


# BASIC SHANKS HSK-A DIN 69893/1 MODULAR WITH LATERAL CLAMPING<sup>[1]</sup> AND RADIAL ADJUSTMENT



Max radial adjustment  $\pm 0,2$  mm on  $\varnothing$

ORDER CODE	HSK	MODULAR REDUCER D	L	STANDARD EQUIPMENT			ACCESSORIES			
				wedges+OR	clamping screw	adjusting dowels	clamping screw key	tang key <sup>[2]</sup>	key kit clutch for coolant	kit clutch for coolant <sup>[3]</sup>
HSK-A.63.50L.70	63	50	70	ATR14102.2.3	ATR14102.1	M8x1x10G	hexagon 6	fixed 18 ATT14103	ATR23856	ATT23728
HSK-A.63.63L.75	63	63	75	ATR41613.4	ATR14108.1	M8x1x14G	hexagon 6	fixed 24 ATT14104	ATR23856	ATT23728
HSK-A.100.50L.80	100	50	80	ATR14102.2.3	ATR14102.1	M8x1x10G	hexagon 6	fixed 18 ATT14103	ATR23856	ATT23656
HSK-A.100.63L.80	100	63	80	ATR14108.2.3	ATR14108.1	M8x1x14G	hexagon 6	fixed 24 ATT14104	ATR23856	ATT23656
HSK-A.100.80L.80	100	80	80	ATR18775.2.3	ATR18775.1	M8x1x20G	hexagon 6	fixed 24 ATT14104	ATR23856	ATT23656

- [1]** The modular system has lateral clamping which enables efficient quick release of the tools.  
Light torque exerted on the clamping screw transmits high axial forces which provide stiffness and extreme accuracy to the assembly.
- [2]** All adaptors and tools with modular shanks require their respective tang fitted before assembly to the system with lateral clamping.
- [3]** Coolant clutch kits are supplied separately on request.