



Ricambi per ganasce STANDARD / Spares for STANDARD jaws

Tipo (grandezza) morsa / Vise (type) size

1 2 3 4 5 6

PIASTRE TEMPRATE RIGATE O QUADRETTATE

HARDENED GROOVED OR SERRATED JAW PLATES


cad / each

Per qualsiasi piastra ganascia speciale, raddoppiare il prezzo / For special taylor made jaw plate double the price


Standard



A richiesta / On request

**Art. 230** (W)**Art. 230S** (W)Per ganascia fissa e mobile - Art. 120, 126, 127 - Larghezza normale (W)
For fixed and movable jaw - Art. 120, 126, 127 - Normal width (W)**Art. 231** (W2)**Art. 231S** (W2)Per ganascia fissa e mobile - Art. 121, 128, 129 - Larghezza ridotta (W2)
For fixed and movable jaw - Art. 121, 128, 129 - Narrow width (W2)

Standard

A richiesta
On request**Art. 248** (W)**Art. 248S** (W)Per ganascia fissa doppia Art. 123 - Larghezza normale (W)
For double fixed jaw Art. 123 - Normal width (W)**Art. 249** (W2)**Art. 249S** (W2)Per ganascia fissa doppia Art. 124 - Larghezza ridotta (W2)
For double fixed jaw Art. 124 - Narrow width (W2)

	W	100	125	150	175	200	300
	W2	74	94	124	144	169	194
	A	14	20	24	24	29	35
	B2	24,5	32	40	40	53	63
	C	20	32	50	50	76	90

Cod. Art. 230	1.65.10000	1.65.20000	1.65.30000	1.65.40000	1.65.50000	1.65.60000
Cod. Art. 230S	4.23.0S100	4.23.0S200	4.23.0S300	4.23.0S400	4.23.0S500	4.23.0S600

Cod. Art. 231	1.65.11000	1.65.21000	1.65.31000	1.65.41000	1.65.51000	1.65.61000
Cod. Art. 231S	4.23.1S100	4.23.1S200	4.23.1S300	4.23.1S400	4.23.1S500	4.23.1S600


Cod. Art. 248	1.65.14000	1.65.24000	1.65.34000	1.65.44000	1.65.54000	1.65.64000
Cod. Art. 248S	4.24.8S100	4.24.8S200	4.24.8S300	4.24.8S400	4.24.8S500	4.24.8S600

Cod. Art. 249	1.65.15000	1.65.25000	1.65.35000	1.65.45000	1.65.55000	1.65.65000
Cod. Art. 249S	4.24.9S100	4.24.9S200	4.24.9S300	4.24.9S400	4.24.9S500	4.24.9S600

Cod. Art. 232	1.65.10100	1.65.20100	1.65.30100	1.65.40100	1.65.50100	1.65.60100
Cod. Art. 233	1.65.11100	1.65.21100	1.65.31100	1.65.41100	1.65.51100	1.65.61100

**Art. 232** (W)Per ganascia fissa e mobile - Art. 120, 127, 129 - Larghezza normale (W)
For fixed and movable jaw - Art. 120, 127, 129 - Normal width (W)**Art. 233** (W2)Per ganascia fissa e mobile - Art. 121, 128, 129 - Larghezza ridotta (W2)
For fixed and movable jaw - Art. 121, 128, 129 - Narrow width (W2)**Art. 250** (W)Per ganascia fissa doppia Art. 123 - Larghezza normale (W)
For double fixed jaw Art. 123 - Normal width (W)**Art. 251** (W2)Per ganascia fissa doppia Art. 124 - Larghezza ridotta (W2)
For double fixed jaw Art. 124 - Narrow width (W2)


Cod. Art. 250	1.65.14100	1.65.24100	1.65.34100	1.65.44100	1.65.54100	1.65.64100
Cod. Art. 251	1.65.15100	1.65.25100	1.65.35100	1.65.45100	1.65.55100	1.65.65100



Cod. Art. 234	1.65.10200	1.65.20200	1.65.30200	1.65.40200	1.65.50200	1.65.60200
Cod. Art. 235	1.65.11200	1.65.21200	1.65.31200	1.65.41200	1.65.51200	1.65.61200



Cod. Art. 252	1.65.14200	1.65.24200	1.65.34200	1.65.44200	1.65.54200	1.65.64200
Cod. Art. 253	1.65.15200	1.65.25200	1.65.35200	1.65.45200	1.65.55200	1.65.65200

**Art. 252** (W)Per ganascia fissa doppia Art. 123 - Larghezza normale (W)
For double fixed jaw Art. 123 - Normal width (W)**Art. 253** (W2)Per ganascia fissa doppia Art. 124 - Larghezza ridotta (W2)
For double fixed jaw Art. 124 - Super narrow width (W2)