


Tipo (grandezza) morsa / Vise (type) size			1	2	3	
Art. 608A	Ganascia fissa con gradino / Fixed jaw with step		Cod.	6.60.8A100	6.60.8A200	6.60.8A300
Art. 613A	Ganascia mobile / Movable jaw		Cod.	6.61.3A100	6.61.3A200	6.61.3A300
Art. 613B	Cuneo di spinta / Clamping wedge		Cod.	6.61.3B100	6.61.3B200	6.61.3B300
Art. 613C	Dado a "T" / "T" nut		Cod.	6.61.3C100	6.61.3C200	6.61.3C300
Art. 613D	Vite TCEI / Hex socket head screw		Cod.	6.61.3D100	6.61.3D200	6.61.3D300
Art. 613E	Grano / Set screw		Cod.	6.61.3E100	6.61.3E200	6.61.3E300
Art. 613F	Molla / Spring		Cod.	6.61.3F100	6.61.3F200	6.61.3F300
Art. 615A	Cuneo di posizionamento liscio maggiorato Positioning wedge smooth (increased with respect to stand dimension)		Cod.	6.61.5A100	6.61.5A200	6.61.5A300
Art. 615AS	Cuneo di posizionamento zigrinato maggiorato Positioning wedge serrated (increased with respect to stand dimension)		Cod.	6.61.5AS10	6.61.5AS20	6.61.5AS30
Art. 615I	Cuneo di posizionamento dolce maggiorato Positioning wedge soft (increased with respect to stand dimension)		Cod.	6.61.5I100	6.61.5I200	6.61.5I300
Art. 615L	Cuneo di posizionamento a gradino maggiorato Positioning wedge with stop (increased with respect to stand dimension)		Cod.	6.61.5L100	6.61.5L200	6.61.5L300
Art. 615C	Vite TCEI fissaggio ganascia fissa Hex socked head screw for fixed jaw		Cod.	6.61.5C100	6.61.5C200	6.61.5C300
Art. 615E	Vite TCEI TCEI screw		Cod.	6.61.5E100	6.61.5E200	6.61.5E300

Art. 613Ganascia mobile di spinta
Clamping movable jaws**Art. 615**Ganascia con cuneo di posizionamento maggiorato
Jaw with bigger positioning wedge
(Increased with respect to standard dimensions)