



0691 DIGI-MET® Indicators



Model

- Aluminium housing
- Outer ring (Bezel) Ø 60 mm
- Replacement probe tip M 2.5
- Protection class IP51
- Water and coolant resistant
- Clamping shank Ø 8 mm
- Display unit can be rotated through 270°
- LCD display with 11 mm high numerals
- Factory standard

Functions

- ON / OFF
- Set to zero at any point
- mm / inch switching
- PRESET-Function (setting a numerical value)
- Reversal of counting direction
- Data interface RS232 Proximity (cable no. 1998 760)

* Additional functions models 0691 751 + 0691 753

- TOL (tolerance value input)
- Factor input
- MIN / MAX
- TIR (MIN-MAX differential)

Delivery

- Cardboard box



0691 733



0691 735



0691 747



		Measuring span	Resolution		Error limit	Order no.	List price
		mm	mm	inch	mm		EUR
Reading 0.01 mm							
		12.5	0.01	.0005	0.01	0691 731	363.00
		25	0.01	.0005	0.01	0691 733	416.00
		50	0.01	.0005	0.02	0691 735	905.00
		100	0.01	.0005	0.02	0691 737	1020.00
Reading 0.001 mm							
		12.5	0.001	.00005	0.004	0691 741	448.00
		25	0.001	.00005	0.005	0691 743	491.00
		50	0.001	.00005	0.007	0691 745	1003.00
		100	0.001	.00005	0.008	0691 747	1158.00
Reading 0.001 mm. with additional functions*							
		12.5	0.001	.00005	0.003	0691 751	521.00
		25	0.001	.00005	0.004	0691 753	576.00