

0907 Set of DIGI-MET® 2/3 point internal micrometers



Specification



- DIN 863-4
- Reading: 0.001 mm / .00005 inch
- Protection class IP67
- LCD display
- Certificate for setting ring and internal micrometers
- Ratchet stop
- For through holes
- From measuring range 12.5 mm for through and blind holes
- From measuring range 12.5 mm with carbide tipped measuring faces

Electronic functions

- ON/OFF switch
- Zero setting at any position
- mm/inch conversion
- Data output: 2 versions to choose (see table)
 - serial interface RS 232
 - Power
 - wireless data transfer via bluetooth
- Max/Min value memory
- Hold Function
- PRESET Function (setting a numerical value)
- Tolerance function

Shipment

- Wooden case
- With setting rings

| | | Measuring range mm | Setting ring dia. mm | Ref. No. without Bluetooth | List price Euro | Ref. No. * Bluetooth | List price Euro |
|------------------------------------|--|--------------------|----------------------|----------------------------|-----------------|----------------------|-----------------|
| 2 Point internal micrometer | | | | | | | |
| ▪ | | 2 - 6 | 2.5 / 4.0 / 5.0 | 0907 751 | 3,408.00 | 0907 851 | 3,483.00 |
| 3 Point internal micrometer | | | | | | | |
| ▪ | | 6 - 10 | 8.0 | 0907 753 | 1,359.00 | 0907 853 | 1,434.00 |
| ▪ | | 10 - 20 | 12.5 / 20.0 | 0907 755 | 1,644.00 | 0907 855 | 1,719.00 |
| ▪ | | 20 - 50 | 20.0 / 35.0 | 0907 757 | 2,266.00 | 0907 857 | 2,341.00 |
| ▪ | | 50 - 100 | 65.0 / 80.0 | 0907 759 | 2,519.00 | 0907 859 | 2,594.00 |
| ▪ | | 100 - 150 | 125.0 | 0907 761 | 2,114.00 | 0907 861 | 2,189.00 |
| ▪ | | 150 - 200 | 125.0 | 0907 763 | 2,826.00 | 0907 863 | 2,901.00 |
| ▪ | | 100 - 200 | 125.0 / 175.0 | 0907 775 | 4,437.00 | 0907 875 | 4,512.00 |

Accessories

| | Ref. No. | List price Euro |
|---|----------|-----------------|
| Battery, 3V-Lithium, CR 2032 | 0220 704 | 3.60 |
| USB-Keyboard interface cable RS 232 Power | 0997 774 | 283.00 |
| Bluetooth receiver | 1998 750 | 125.00 |

Measuring depth extensions for 2/3 point internal micrometers 0907-0908



Specification

- Suitable for gauges 0907 and 0908

| | | Measuring range mm | Length mm | Ref. No. | List price Euro |
|---|--|--------------------|-----------|----------|-----------------|
| ▪ | | 6 - 10 | 63 | 0909 506 | 78.00 |
| ▪ | | 10 - 12.5 | 76 | 0909 508 | 78.00 |
| ▪ | | 12.5 - 20 | 100 | 0909 509 | 78.00 |
| ▪ | | 20 - 50 | 150 | 0909 511 | 114.00 |
| ▪ | | 50 - 300 | 150 | 0909 514 | 134.00 |

0908 Set of DIGI-MET® 2/3 point internal micrometers



Specification



- DIN 863-4
- Reading: 0.001 mm / .00005 inch
- Protection class IP67
- With pistol grip
- From measuring range 12.5 mm with carbide tipped measuring faces
- Rotateable LCD display
- Certificate for setting ring and micrometer
- For through holes
- From measuring range 12.5 mm for through and blind holes

Electronic functions

- ON/OFF switch
- Zero setting at any position
- mm/inch conversion
- Data output: 2 versions to choose (see table) - serial interface RS 232 Power - wireless data transfer via bluetooth
- Max/Min value memory
- Hold Function
- PRESET Function (setting a numerical value)
- Tolerance function

Shipment

- Wooden case
- With setting rings
- Calibration according to table

| ✂ | 📏 | Measuring range | | Setting ring dia. mm | Ref. No. without Bluetooth | List price Euro | Ref.No. ✂ Bluetooth | List price Euro |
|--|---|-----------------|-------------|---------------------------|-------------------------------|--------------------|------------------------|--------------------|
| | | mm | inch | | | | | |
| 2 Point instant internal micrometer | | | | | | | | |
| ▪ | | 2 - 6 | .080 - .250 | 2.5 / 4.0 / 5.0 | 0908 751 | 3,749.00 | 0908 851 | 3,824.00 |
| 3 Point instant internal micrometer | | | | | | | | |
| ▪ | | 6 - 10 | 1/4 - 3/8 | 8.0 | 0908 753 | 1,407.00 | 0908 853 | 1,482.00 |
| ▪ | | 10 - 20 | 3/8 - 3/4 | 12.5 / 20.0 | 0908 755 | 1,662.00 | 0908 855 | 1,737.00 |
| ▪ | | 20 - 50 | 3/4 - 2 | 20.0 / 35.0 | 0908 757 | 2,177.00 | 0908 857 | 2,252.00 |
| ▪ | | 20 - 100 | 3/4 - 4 | 20.0 / 35.0 / 65.0 / 80.0 | 0908 773 | 3,613.00 | 0908 873 | 3,688.00 |
| ▪ | | 50 - 100 | 2 - 4 | 65.0 / 80.0 | 0908 759 | 2,438.00 | 0908 859 | 2,513.00 |
| ▪ | | 100 - 150 | 4 - 6 | 125.0 | 0908 761 | 2,177.00 | 0908 861 | 2,252.00 |
| ▪ | | 150 - 200 | 6 - 8 | 175.0 | 0908 763 | 2,909.00 | 0908 863 | 2,984.00 |
| ▪ | | 100 - 200 | 4 - 8 | 125.0 / 175.0 | 0908 775 | 4,607.00 | 0908 875 | 4,682.00 |

Accessories

| | Ref. No. | List price Euro |
|---|----------|--------------------|
| Battery, 3V-Lithium, CR 2032 | 0220 704 | 3.60 |
| USB-Keyboard interface cable RS 232 Power | 0997 774 | 283.00 |
| Bluetooth receiver | 1998 750 | 125.00 |

Measuring depth extensions for 2/3 point internal micrometers 0907-0908



Specification

- Suitable for all internal micrometers from series 0907 and 0908

| ✂ | 📏 | Measuring range mm | | Length mm | Ref. No. | List price Euro |
|---|---|-----------------------|--------|--------------|----------|--------------------|
| ▪ | | 6 | - 10 | 63 | 0909 506 | 78.00 |
| ▪ | | 10 | - 12.5 | 76 | 0909 508 | 78.00 |
| ▪ | | 12.5 | - 20 | 100 | 0909 509 | 78.00 |
| ▪ | | 20 | - 50 | 150 | 0909 511 | 114.00 |
| ▪ | | 50 | - 300 | 150 | 0909 514 | 134.00 |