



0864 Disc micrometers to measure gear tooth



DIN
863-3

Model

- DIN 863-3
- Reading: 0.01 mm
- Reading parts are satin chrome finished
- Modul 0.8 - 6
- Ratchet stop
- Hardened measuring faces
- Locking ring
- Friction coupling
- Thermally insulated

Delivery

- Wooden case

Measuring range mm	Disc dia. mm	Pitch mm	Thimble dia. mm	Error limit mm	Order no.	List price EUR
0 - 25	25	0.5	20	0.004	0864 321	317.00
25 - 50	25	0.5	20	0.004	0864 322	380.00
50 - 75	25	0.5	20	0.005	0864 323	412.00
75 - 100	25	0.5	20	0.005	0864 324	447.00
100 - 125	25	0.5	20	0.006	0864 325	483.00
125 - 150	25	0.5	20	0.006	0864 326	517.00
150 - 175	25	0.5	20	0.007	0864 327	556.00
175 - 200	25	0.5	20	0.007	0864 328	594.00

0933 DIGI-MET® Disc micrometers to measure gear tooth



OPTO

Model

- Factory standard
- Selectable resolution 0.01 mm / 0.001 mm; 0.0005 inch / 0.00005 inch
- Non-rotating spindle
- Linear measuring system
- Locking lever
- Thermally insulated
- Ratchet stop

Functions

- ON / OFF
- Set to zero at any point
- mm / inch switching
- MIN / MAX
- Hold
- PRESET-Function (setting a numerical value)
- TOL (tolerance value input)
- Data output Opto RS 232

Delivery

- Wooden case

Measuring range mm	inch	Disc dia. mm	Module	Pitch mm	Spindle dia. mm	Order no.	List price EUR
0 - 25	0 - 1	25	0.4	1	8	0933 701	779.00
25 - 50	1 - 2	25	0.4	1	8	0933 702	857.00
50 - 75	2 - 3	25	0.4	1	8	0933 703	909.00
75 - 100	3 - 4	25	0.4	1	8	0933 704	961.00
100 - 125	4 - 5	30	0.6	1	8	0933 705	1013.00
125 - 150	5 - 6	30	0.6	1	8	0933 706	1065.00
150 - 175	6 - 7	30	0.6	1	8	0933 707	1117.00
175 - 200	7 - 8	30	0.6	1	8	0933 708	1195.00



Accessories

Order no.	List price EUR
Battery, 3V-Lithium, CR 2032	0220 704 3.70
Data cable opto to RS232	0996 701 74.00
Data cable opto to USB	0996 705 141.00
USB-keyboard interface cable	0997 770 241.00