



1320 DIGI-MET® Pocket calipers



1320 416



1320 517



Model

- Inductive measuring system, resistant to damp and sweat
- Stainless steel
- LCD display 11 mm without data output, 7.5 mm with data output
- DIN 862
- Locking screw
- Inside cross points

- Four way measurement with measuring ranges 150 and 200 mm
- Three way measurement with measuring range 300 mm

Functions

- ON / OFF
- Quick-Start
- Quick-Lock (key lock)
- Set to zero at any point
- mm / inch switching
- PRESET-Function (setting a numerical value)

Delivery

- Plastic case

		Measuring range		Jaw length		Reading		Error limit	Depth gauge	Order no.	List price
		mm	inch	mm	inch	mm	inch	mm	mm		EUR
Without data output											
▪		0 - 150	0 - 6	40	1.6	0.01	.0005	0.03	round 1.5	1320 416	109.00
▪		0 - 150	0 - 6	40	1.6	0.01	.0005	0.03	rect.	1320 417	109.00
With DATA VARIABLE											
▪		0 - 150	0 - 6	40	1.6	0.01	.0005	0.03	round 1.5	1320 516	142.00
▪		0 - 150	0 - 6	40	1.6	0.01	.0005	0.03	rect.	1320 517	142.00
▪		0 - 200	0 - 8	50	2.0	0.01	.0005	0.03	rect.	1320 519	179.00
▪		0 - 300	0 - 12	65	2.5	0.01	.0005	0.03	none	1320 522	230.00
With DATA VARIABLE, with extra long cross tips (40 mm)											
▪		0 - 150	0 - 6	40	1.6	0.01	.0005	0.03	round 1.5	1320 518	384.00



1998720

1998501

1997501

Accessories

	Order no.	List price EUR
Battery, 3V-Lithium, CR 2032	0220 704	3.70
Data cable DATA VARIABLE to digimatic	1998 501	61.00
Data cable DATA VARIABLE to RS232	1997 501	48.00
Data cable DATA VARIABLE to USB	1998 720	69.00