



1342 / 1343 DIGI-MET® Workshop calipers IP65



Model

- Stainless steel
- Inductive measuring system, protection class IP65
- DIN 862
- LCD display:
 - 10 mm with measuring range 300 mm;
 - 12.5 mm from measuring range 500 mm
- Locking screw

Functions

- ON / OFF
- **Quick-Start**
- **Quick-Lock** (key lock)
- Set to zero at any point
- mm / inch switching
- PRESET-Function (setting a numerical value)
- Variable data output RS 232 + Digimatic + USB

Delivery

- Wooden case

		Measuring range		Jaw length		Reading		Error limit	Order no.	List price
		mm	inch	mm	inch	mm	inch	mm		EUR
Without fine adjustment										
▪		0 - 300	0 - 12	90	3.5	0.01	.0005	0.03	1342 522	380.00
▪		0 - 500	0 - 20	125	5.0	0.01	.0005	0.03	1342 528	702.00
▪		0 - 800	0 - 31	150	6.0	0.01	.0005	0.04	1342 532	971.00
▪		0 - 1000	0 - 39	150	6.0	0.01	.0005	0.04	1342 534	1208.00
With fine adjustment										
▪		0 - 300	0 - 12	90	3.5	0.01	.0005	0.03	1343 522	434.00
▪		0 - 500	0 - 20	125	5.0	0.01	.0005	0.03	1343 528	756.00
▪		0 - 800	0 - 31	150	6.0	0.01	.0005	0.04	1343 532	1025.00
▪		0 - 1000	0 - 39	150	6.0	0.01	.0005	0.04	1343 534	1261.00



Accessories

	Order no.	List price EUR
Battery, 3V-Lithium, CR 2032	0220 704	3.70
Data cable DATA VARIABLE to USB	1998 720	69.00
Data cable DATA VARIABLE to RS232	1997 501	48.00
Data cable DATA VARIABLE to digimatic	1998 501	61.00