



1360 DIGI-MET® Depth gauges



Model

- Stainless steel
- Protection class IP67
- LCD display 7.5 mm
- DIN 862
- Locking screw
- Straight measuring rod

Functions

- ON / OFF
- **Quick-Start**
- **Quick-Lock** (key lock)
- Set to zero at any point
- mm / inch switchin
- Variable data output RS 232 + Digimatic + USB

Delivery

- Wooden case

	Measuring range		Base length	Reading		Error limit	Order no.	List price
	mm	inch	mm	mm	inch	mm		EUR
▪	0 - 150	0 - 6	100	0.01	.0005	0.03	1360 716	316.00
▪	0 - 200	0 - 8	100	0.01	.0005	0.03	1360 718	358.00
▪	0 - 300	0 - 12	150	0.01	.0005	0.03	1360 722	402.00
▪	0 - 500	0 - 20	150	0.01	.0005	0.03	1360 728	462.00
▪	0 - 1000	0 - 39	250	0.01	.0005	0.04	1360 734	1315.00
▪	0 - 1500	0 - 59	250	0.01	.0005	0.05	1360 738	2006.00
▪	0 - 2000	0 - 80	250	0.01	.0005	0.06	1360 740	2381.00



1998720 1997501 1998501

Accessories

	Order no.	List price EUR
Battery, 3V-Lithium, CR 2032	0220 704	3.70
Data cable DATA VARIABLE to RS232	1997 501	48.00
Data cable DATA VARIABLE to digimatic	1998 501	61.00
Data cable DATA VARIABLE to USB	1998 720	69.00