



1722 / 1723 / 1724 DIGI-MET® Indicators



1722 502



1723 502



1724 502

Model

- Housing Ø 60 mm
- Replacement probe tip M 2.5
- Protection class IP52
- Clamping shank Ø 8 mm
- LCD display with 12 mm high numerals
- Accuracy according to factory standard

Functions

- ON / OFF
- **Quick-Start**
- **Quick-Lock** (key lock)
- Set to zero at any point
- Reversal of counting direction
- mm / inch switching
- Individual key lock

Delivery

- Cardboard box

Marked	%	Measuring span	Resolution mm		Error limit	Measuring force	Order no.	List price
		mm	mm	inch	mm	N		EUR
		12.5	0.01	.0005	0.02	0.5 - 1	1722 502	138.00
		12.5	0.005	.0001	0.015	0.5 - 1	1723 502	174.00
		12.5	0.001	.00005	0.005	0.5 - 1	1724 502	284.00



1998720



1997501



1998501



1739920

Accessories

	Order no.	List price
Battery, 3V-Lithium, CR 2032	0220 704	3.70
Data cable DATA VARIABLE to USB	1998 720	69.00
Data cable DATA VARIABLE to RS232	1997 501	48.00
Data cable DATA VARIABLE to digimatic	1998 501	61.00
Cable release	1739 920	14.30