



1726 / 1728 DIGI-MET® Indicators



1726 502



1728 502



Model

- Aluminium housing
- Hardened stainless steel spindle
- Outer ring (Bezel) Ø 60 mm
- Replacement probe tip M 2.5
- Protection class IP42
- Clamping shank Ø 8 mm
- Display unit can be rotated through 280°
- LCD display with 11 mm high numerals
- Factory standard

Functions

- ON / OFF
- Quick-Start
- Quick-Lock (key lock)
- Set to zero at any point
- mm / inch switching
- ABS (display can be set to zero without losing the Preset value)
- TOL (tolerance value input)
- Reversal of counting direction
- Factor input
- Individual key lock
- PRESET-Function (setting a numerical value)
- Variable data output RS 232 + Digimatic + USB

Delivery

- Cardboard box

✕	%	Measuring span	Resolution		Error limit		Repeatability	Measuring force	Order no.	List price
		mm	mm	inch	total span mm	partial span**mm	mm	N		
Reading 0.001 mm										
		12.5	0.001	.00005	0.004	0.002	0.001	0.65 - 0.9	1726 502	331.00
		25	0.001	.00005	0.004	0.002	0.001	0.65 - 1.15	1726 506	365.00
		50	0.001	.00005	0.007	0.002	0.001	1.25 - 2.7	1726 510	642.00
		100	0.001	.00005	0.008	0.002	0.001	1.6 - 3.5	1726 514	795.00
Reading 0.01 mm										
		12.5	0.01	.0005	0.02	-	0.01	0.65 - 0.9	1728 502	277.00
		25	0.01	.0005	0.02	-	0.01	0.65 - 1.15	1728 506	353.00
		50	0.01	.0005	0.02	-	0.01	1.25 - 2.7	1728 510	576.00
		100	0.01	.0005	0.02	-	0.01	1.6 - 3.5	1728 514	737.00

* Reading switchable: 0.0005 / 0.001 / 0.002 / 0.005 / 0.010 mm

** Partial span= 25 steps by step value 0.0005 mm



1998720

1998501

1997501

1739910

Accessories

	Order no.	List price EUR
Battery, 3V-Lithium, CR 2450	1998 770	5.70
Data cable DATA VARIABLE to USB	1998 720	69.00
Data cable DATA VARIABLE to RS232	1997 501	48.00
Data cable DATA VARIABLE to digimatic	1998 501	61.00
Cable release	1739 910	38.40