



1730 / 1732 DIGI-MET® Indicators



Model

- Aluminium housing
- Outer ring (Bezel) Ø 60 mm
- Replacement probe tip M 2.5
- Protection class IP54
- Clamping shank Ø 8 mm
- Display unit can be rotated through 280°
- LCD display with 11 mm high numerals
- Factory standard

Functions

- ON / OFF
- Quick-Start
- Quick-Lock (key lock)
- Set to zero at any point
- mm / inch switching
- ABS (display can be set to zero without losing the Preset value)
- TOL (tolerance value input)
- Reversal of counting direction

Delivery

- Cardboard box

✕	%	Measuring span	Resolution		Error limit		Repeatability	Measuring force	Order no.	List price
		mm	mm	inch	total span mm	partial span**mm	mm	N		EUR
		12.5	0.001	.00005	0.004	0.002	0.001	0.65 - 0.9	1730 502	367.00
		25	0.001	.00005	0.004	0.002	0.001	0.65 - 1.15	1730 506	414.00
		12.5	0.01	.0005	0.02	-	0.01	0.65 - 1.4	1732 502	310.00
		25	0.01	.0005	0.02	-	0.01	1 - 2.25	1732 506	391.00

* Reading switchable: 0.0005 / 0.001 / 0.002 / 0.005 / 0.010 mm

** Partial span= 25 steps by step value 0.0005 mm



Accessories

	Order no.	List price EUR
Battery, 3V-Lithium, CR 2450	1998 770	5.70
Data cable DATA VARIABLE to USB	1998 720	69.00
Data cable DATA VARIABLE to RS232	1997 501	48.00
Data cable DATA VARIABLE to digimatic	1998 501	61.00
Cable release	1739 910	38.40