

WATERPROOF DIGITAL CALIPERS

ATTENTION: IT IS NECESSARY TO SET ZERO AFTER POWER ON EACH TIME

ATTENTION: NO DATA OUTPUT


IP67 WATERPROOF

- IP67 dust/waterproof
- Resolution: 0.01mm/0.0005"
- Button function: zero, on/off, mm/inch, ABS/REL, hold
- Battery CR2032
- Meet DIN862
- Made of stainless steel

INSPECTION
CERTIFICATE
TRACEABLE TO DKD



1118-150B



Code	Range	Accuracy	Thumb roller	L	a	b	c	d
1118-150B*	0-150mm/0-6"	±0.03mm	with	236	21	16	16	40
1118-200B*	0-200mm/0-8"	±0.03mm	with	286	24	19	16	50
1118-300B*	0-300mm/0-12"	±0.03mm	with	400	25	20.5	17	60
1118-150BW*	0-150mm/0-6"	±0.03mm	without	236	21	16	16	40
1118-200BW*	0-200mm/0-8"	±0.03mm	without	286	24	19	16	50
1118-300BW*	0-300mm/0-12"	±0.03mm	without	400	25	20.5	17	60

* Supplied with manufacturer inspection certificate traceable to DKD Germany

DIGITAL CALIPERS (ABSOLUTE CODE)

INSPECTION
CERTIFICATE
TRACEABLE TO DKD

HIGH
PRECISION


ABSOLUTE
CODE

DATA
OUTPUT

- Absolute code
- Resolution: 0.01mm/0.0005"
- Buttons: mm/inch, ABS/REL, on/off, origin set
- Battery CR2032, automatic power off
- After automatic power off, move the digital unit to turn on power
- Data output
- Meet DIN862
- Made of stainless steel
- Optional accessory: data output cable (code 7302-SPC4)



1103-150



Code	Range	Accuracy	Thumb roller	L	a	b	c	d
1103-150*	0-150mm/0-6"	±0.02mm	with	234	20	15	16	40
1103-200*	0-200mm/0-8"	±0.02mm	with	286	24	19	16	50
1103-300*	0-300mm/0-12"	±0.03mm	with	390	26	21.5	16	60
1103-150W*	0-150mm/0-6"	±0.02mm	without	234	20	15	16	40
1103-200W*	0-200mm/0-8"	±0.02mm	without	286	24	19	16	50
1103-300W*	0-300mm/0-12"	±0.03mm	without	390	26	21.5	16	60

* Supplied with manufacturer inspection certificate traceable to DKD Germany

DIGITAL CALIPERS


INSPECTION
CERTIFICATE
TRACEABLE TO DKD

ATTENTION:
NO DATA OUTPUT

- Zinc alloy housing for digital unit
- Resolution: 0.01mm/0.0005"
- Buttons: zero, on/off, mm/inch
- Automatic power off, move the digital unit to turn on power
- Battery CR2032
- Meet DIN862
- Made of stainless steel



1114-150A



Code	Range	Accuracy	Thumb roller	L	a	b	c	d
1114-150A*	0-150mm/0-6"	±0.03mm	with	236	21	16	16	40
1114-200A*	0-200mm/0-8"	±0.03mm	with	286	24	19	16	50
1114-300A*	0-300mm/0-12"	±0.03mm	with	400	25	20.5	17	60
1114-150AW*	0-150mm/0-6"	±0.03mm	without	236	21	16	16	40
1114-200AW*	0-200mm/0-8"	±0.03mm	without	286	24	19	16	50
1114-300AW*	0-300mm/0-12"	±0.03mm	without	400	25	20.5	17	60

* Supplied with manufacturer inspection certificate traceable to DKD Germany