

DIGITAL CALIPERS WITH CARBIDE TIPPED JAWS


- Carbide tipped jaws for inside and outside measurements
- Resolution: 0.01mm/0.0005"
- Buttons: on/off, zero, mm/inch
- Automatic power off, move the digital unit to turn on power
- Battery CR2032, data output, meet DIN862
- Made of stainless steel
- Optional accessory: data output cable
(code 7306-20, 7302-SPC5A/SPC5B, 7305-SPC2A)

**INSPECTION
CERTIFICATE**
TRACEABLE TO DKD

DATA
OUTPUT



1110-150A



Code	Range	Accuracy	Thumb roller	L	a	b	c	d
1110-150A*	0-150mm/0-6"	±0.03mm	with	236	21	16	16	40
1110-200A*	0-200mm/0-8"	±0.03mm	with	286	24	19	16	50
1110-300A*	0-300mm/0-12"	±0.03mm	with	400	25	20.5	16	60
1110-150AW*	0-150mm/0-6"	±0.03mm	without	236	21	16	16	40
1110-200AW*	0-200mm/0-8"	±0.03mm	without	286	24	19	16	50
1110-300AW*	0-300mm/0-12"	±0.03mm	without	400	25	20.5	16	60

* Supplied with manufacturer inspection certificate traceable to DKD Germany

DIGITAL CALIPERS WITH CERAMIC TIPPED JAWS

- Ceramic tipped jaws for outside measurement, extremely wear-resistant, non-magnetic, non-conductive
- Resolution: 0.01mm/0.0005"
- Buttons: on/off, zero, mm/inch
- Automatic power off, move the digital unit to turn on power
- Battery CR2032, data output, made of stainless steel
- Meet DIN862
- Optional accessory: data output cable
(code 7306-20, 7302-SPC5A/SPC5B, 7305-SPC2A)

ceramic
tipped jaws




**INSPECTION
CERTIFICATE**
TRACEABLE TO DKD

DATA
OUTPUT



1193-150



Code	Range	Accuracy	Thumb roller	L	a	b	c	d
1193-150*	0-150mm/0-6"	±0.03mm	with	235	21	16.5	16	40
1193-200*	0-200mm/0-8"	±0.03mm	with	297	24	20	16	50
1193-300*	0-300mm/0-12"	±0.03mm	with	390	26	21.5	16	60
1193-150W*	0-150mm/0-6"	±0.03mm	without	235	21	16.5	16	40
1193-200W*	0-200mm/0-8"	±0.03mm	without	297	24	20	16	50
1193-300W*	0-300mm/0-12"	±0.03mm	without	390	26	21.5	16	60

* Supplied with manufacturer inspection certificate traceable to DKD Germany

LEFT HAND DIGITAL CALIPERS


- Designed for left handed users
- Resolution: 0.01mm/0.0005"
- Buttons: on/off, zero, mm/inch
- Automatic power off, move the digital unit to turn on power
- Battery CR2032
- Data output
- Meet DIN862
- Made of stainless steel
- Optional accessory: data output cable
(code 7306-20, 7302-SPC5A/SPC5B, 7305-SPC2A)

**INSPECTION
CERTIFICATE**
TRACEABLE TO DKD

DATA
OUTPUT



1130-150



Code	Range	Accuracy	Thumb roller	L	a	b	c	d
1130-150*	0-150mm/0-6"	±0.03mm	with	236	21	16	16	40
1130-200*	0-200mm/0-8"	±0.03mm	with	286	24	19	16	50
1130-300*	0-300mm/0-12"	±0.03mm	with	400	25	20.5	17	60
1130-150W*	0-150mm/0-6"	±0.03mm	without	236	21	16	16	40
1130-200W*	0-200mm/0-8"	±0.03mm	without	286	24	19	16	50
1130-300W*	0-300mm/0-12"	±0.03mm	without	400	25	20.5	17	60

* Supplied with manufacturer inspection certificate traceable to DKD Germany