WATERPROOF DIGITAL CALIPERS

ATTENTION: IT IS NECESSARY TO SET ZERO AFTER POWER ON EACH TIME

ATTENTION: NO DATA OUTPUT



- IP67 dust/waterproof
- Resolution: 0.01mm/0.0005"
- Button function: zero, on/off, mm/inch, ABS/REL, hold
- Battery CR2032
- Meet DIN862
- Made of stainless steel




			(1	mm)	
	а	b	C	d	
36	21	16	16	40	


SPECTION

TRACEABLE TO DKD

Code	Range	Accuracy	Thumb roller	L	а	b	C	d
1118-150B*	0-150mm/0-6"	±0.03mm	with	236	21	16	16	40
1118-200B*	0-200mm/0-8"	±0.03mm	with	286	24	19	16	50
1118-300B*	0-300mm/0-12"	±0.03mm	with	400	25	20.5	17	60
1118-150BW*	0-150mm/0-6"	±0.03mm	without	236	21	16	16	40
1118-200BW*	0-200mm/0-8"	±0.03mm	without	286	24	19	16	50
1118-300BW*	0-300mm/0-12"	±0.03mm	without	400	25	20.5	17	60
		BOOK BOOK BOOK BOOK BOOK BOOK BOOK BOOK	30,180,000,000		E-SSUE	e sensulation		50.50.50







DIGITAL CALIPERS (ABSOLUTE CODE)



- Resolution: 0.01mm/0.0005"
- Buttons: mm/inch, ABS/REL, on/off, origin set
- Battery CR2032, automatic power off

Range

0-150mm/0-6"

0-200mm/0-8"

0-300mm/0-12"

0-150mm/0-6"

0-200mm/0-8"

1103-300W * 0-300mm/0-12" ±0.03mm

- After automatic power off, move the digital unit to turn on power
- Data output

Code

1103-150*

1103-200*

1103-300*

1103-150W *

1103-200W*

- Meet DIN862
- Made of stainless steel
- Optional accessory: data output cable (code 7302-SPC4)

	(mm							
r	L	а	b	C	d			
	234	20	15	16	40			
	286	24	19	16	50			
	390	26	21.5	16	60			
	234		15	16	40			
	286	21	10	16	50			

390 26 21.5 16 60

Accuracy

±0.02mm

±0.02mm

±0.03mm

±0.02mm

±0.02mm

Thumb rolle

with

with

with

without

without

without










1103-150



DIGITAL CALIPERS


INSPECTION CERTIFICATE
TRACEABLE TO DKD

- Zinc alloy housing for digital unit
- Resolution: 0.01mm/0.0005"
- Buttons: zero, on/off, mm/inch
- Automatic power off, move the digital unit to turn on power
- Battery CR2032
- Meet DIN862
- Made of stainless steel

						(mm)		
Code	Range	Accuracy	Thumb roller	L	a	b	C	d
1114-150A*	0-150mm/0-6"	±0.03mm	with	236	21	16	16	40
1114-200A*	0-200mm/0-8"	±0.03mm	with	286	24	19	16	50
1114-300A*	0-300mm/0-12"	±0.03mm	with	400	25	20.5	17	60
1114-150AW*	0-150mm/0-6"	±0.03mm	without	236	21	16	16	40
1114-200AW*	0-200mm/0-8"	±0.03mm	without	286	24	19	16	50
1114-300AW*	0-300mm/0-12"	±0.03mm	without	400	25	20.5	17	60
La contraction de la contracti	The second section from the second second	ALL SOLD STATE OF THE STATE OF		and the same of		· CONSTRUCTION OF		

^{*}Supplied with manufacturer inspection certificate traceable to DKD Germany





Supplied with manufacturer inspection certificate traceable to DKD Germany