

## DATA OUTPUT

# ■ Resolution: 0.01mm/0.0005"

- Buttons: on/off, zero, mm/inch
- Automatic power off, move the digital unit to turn on power
- Battery CR2032
- Data output
- Meet DIN862
- Made of stainless steel
- Optional accessory: data output cable (code 7306-20, 7302-SPC5A/SPC5B, 7305-SPC2A)


							(mn	
Code	Range	Accuracy	Thumb roller	L	а	b	C	d
1108-150*	0-150mm/0-6"	±0.02mm	with	236	21	16	16	40
1108-200*	0-200mm/0-8"	±0.03mm	with	286	24	19	16	50
1108-250*	0-250mm/0-10"	±0.03mm	with	350	25	20.5	16	60
1108-300*	0-300mm/0-12"	±0.03mm	with	400	25	20.5	16	60
1108-150W*	0-150mm/0-6"	±0.02mm	without	236	21	16	16	40
1108-200W*	0-200mm/0-8"	±0.03mm	without	286	24	19	16	50
1108-250W*	0-250mm/0-10"	±0.03mm	without	350	25	20.5	16	60
1108-300W*	0-300mm/0-12"	±0.03mm	without	400	25	20.5	16	60

<sup>\*</sup>Supplied with manufacturer inspection certificate traceable to DKD Germany

# DIGITAL CALIPERS (STANDARD MODEL)



1108-150



# LOCK READING WITH "HOLD" BUTTON

#### DATA OUTPUT

- Resolution: 0.01mm
- Buttons: on/off, zero, hold
- Automatic power off, move the digital unit to turn on power
- Battery CR2032
- Data output
- Meet DIN862
- Made of stainless steel
- Optional accessory: data output cable (code 7306-20, 7302-SPC5A/SPC5B, 7305-SPC2A)

Code	Range	Accuracy	Thumb roller	L	а	b	C	d
1109-150*	0-150mm	±0.03mm	with	236	21	16	16	40
1109-200*	0-200mm	±0.03mm	with	286	24	19	16	50
1109-300*	0-300mm	±0.03mm	with	400	25	20.5	16	60
1109-150W*	0-150mm	±0.03mm	without	236	21	16	16	40
1109-200W*	0-200mm	±0.03mm	without	286	24	19	16	50
1109-300W*	0-300mm	±0.03mm	without	400	25	20.5	16	60


<sup>\*</sup>Supplied with manufacturer inspection certificate traceable to DKD Germany

# METRIC DIGITAL CALIPERS





1109-150



### DATA OUTPUT

### ■ Resolution: 0.01mm/0.0005"

- Buttons: on/off, zero, mm/inch
- Automatic power off, move the digital unit to turn on power
- Battery CR2032
- Data output
- Meet DIN862
- Made of stainless steel
- Optional accessory: data output cable (code 7306-20, 7302-SPC5A/SPC5B, 7305-SPC2A)


							(	(mm)	
Code	Range	Accuracy	Thumb roller						
1119-150*	0-150mm/0-6"	±0.03mm	with	236	21	16	16	40	
1119-150W*	0-150mm/0-6"	±0.03mm	without	236	21	16	16	40	

<sup>\*</sup>Supplied with manufacturer inspection certificate traceable to DKD Germany

## DIGITAL CALIPERS WITH ROUND DEPTH BAR







1119-150

TRACEABLE TO DKD