

+INSIZE+

UNIVERSAL PROTRACTOR




clamp for height gages (optional)




- Parallax-free reading
- Made of stainless steel
- Optional accessory: clamp (code 2372-CLAMP), suitable for height gages 1156, 1351 and 1250

Code	20025430250. * /2006/	Graduation	Accuracy
2372-360	0-360°	5'	±5'

DIAL PROTRACTOR




clamp for height gages (optional)




- Made of stainless steel
- Optional accessory: clamp (code 2372-CLAMP), suitable for height gages 1156, 1351 and 1250

Code	Range	Graduation	Accuracy
2373-360	0-360°	5'	±5'

DIGITAL PROTRACTOR



clamp for height gages (optional)







- Display in degree (for example 32.655°) and
- degree/minute/second (for example 32°39'30")

 SET button: preset the reading, change measuring direction
- MODE button: choose 0~90°, 0~180° or 0~360° display
- ZERO/ON/OFF button: zero and power on/off
 Battery CR2032, automatic power off
- Data output
- Supplied with square to set 90°
- Made of stainless steel
- Optional accessory: data output cable (code 7305-SPC1A), clamp (code 2372-CLAMP), suitable for height gages 1156, 1351 and 1250

		Resolution	Accuracy
2172-360A	0-360°	10"/0.005°	±5'