
BACK PLUNGER TYPE DIAL INDICATORS



- Supplied with handle
 With limit pointers
- Optional accessory: contact points (page 102~103)



2357-5



Code	Range	Graduation	Accuracy	Hysteresis	Range/rev	Dial reading
2357-5*	5mm	0.01mm	15µm	5µm	1mm	0-100

*Supplied with manufacturer inspection certificate traceable to NIST USA

WATERPROOF DIAL INDICATORS



JEWELED BEARING



2324-10

Meet DIN878
IP54 dust/waterproof


Jeweled bearing

Code	Range	Graduation	Accuracy	Hysteresis	Range/rev	Dial reading	Remark
2324-10F*	10mm	0.01mm	17µm	3µm	1mm	0-100	flat back
2324-10*	10mm	0.01mm	17µm	3µm	1mm	0-100	lug back

^{*}Supplied with manufacturer inspection certificate traceable to NIST USA

INSPECTION TRACEABLE TO NIST

TRACEABLE TO NIST



TRACEABLE TO NIST

16

M2.5x0.45

Unit:mm

DOUBLE FACE DIAL INDICATOR



- Read from both sides
- Jeweled bearing
- Supplied with limit pointers
- Optional accessory: contact points (page 102~103)



front



back

2328-10

Code	Range	Graduation	Accuracy	Hysteresis	Range/rev	Dial reading	
2328-10*	10mm	0.01mm	17um	3um	1mm	0-100	

Supplied with manufacturer inspection certificate traceable to NIST USA

