WIDE RANGE THREE POINTS INTERNAL MICROMETERS

- Meet DIN863-4
- Graduation 0.001mm
- Carbide measuring faces
- Ratchet stop
- Setting rings are included (except 200-300mm)


Code	Range	Accuracy	Ø50mm (included) Ø70mm (included)	
3228-70*	50-70mm	5µm		
3228-100*	70-100mm	5µm		
3228-150* 100-150mm		6µm	Ø100mm (included)	
3228-250*	150-250mm	8µm	Ø150mm (included)	
3228-300*	200-300mm	9µm	Ø200mm (optional)	

*Supplied with manufacturer inspection certificate









DIGITAL WIDE RANGE THREE POINTS INTERNAL MICROMETERS

setting ring




- Meet DIN863-4
- Resolution 0.001mm/0.00005"
- IP54 dust/waterproof
- Buttons: on/off, set, mm/inch, ABS/INC
- Data output
- LR44 battery, automatic power off
- Carbide measuring faces
- Ratchet stop
- Supplied with extension rods

Supplied with manufacturer inspection certificate


Setting rings are included (except 200-300mm)
Optional accessary: data output cable (code **7306-30A**, **7302-SPC6**, **7305-SPC3A**)

Code	Range	Accuracy	Setting ring	Extension rod (included)
3128-70*	50-70mm/1.97-2.76"	5µm	Ø50mm (included)	150mm
3128-100*	70-100mm/2.76-3.94"	5µm	Ø70mm (included)	150mm
3128-150*	100-150mm/3.94-5.91"	6µm	Ø100mm (included)	150mm
3128-250*	150-250mm/5.91-9.84"	8µm	Ø150mm (included)	150mm
3128-300*	200-300mm/7.87-11.81"	The state of the s	Ø200mm (optional)	150mm





3128-70



IP54

DATA OUTPUT

INSIDE MICROMETERS

- Graduation 0.01mm
- Ratchet stop
- Carbide measuring faces
- Optional accessary: setting ring (code 6312), micrometer stand and clamp (code 6301 and 6301-1)

Code	Range	Туре	Setting ring	Accuracy
3220-30	5-30mm	Α	5mm (included)	7µm
3220-50	25-50mm	В	25mm (included)	8µm
3220-75	50-75mm	В	50mm (optional)	9µm
3220-100	75-100mm	С	75mm (optional)	10µm

