

+INSIZE+


TAPER GAGES





measure diameter of hole

When measuring diameter of holes, correction on reading is needed due to the thickness of taper gage. For example, when reading A is 14.96mm, diameter ØD is 15mm.




(mm) W

| | 4833-1 | 0.8-15mm | 0.11 |
|---|--------|----------|------|
| Measure opening, slot width, hole diameter, etc. Diameter expection table on the back (only for 1933 1, 1933 2). | 4833-2 | 15-30mm | 0.1n |
| Diameter correction table on the back (only for 4833-1, 4833-2) | 4833-3 | 30-45mm | 0.1n |

| Code | Range | Graduation | Accuracy | L | W |
|--------|----------|------------|----------|-----|------|
| 4833-1 | 0.8-15mm | 0.1mm | ±0.1mm | 146 | 17 |
| 4833-2 | 15-30mm | 0.1mm | ±0.1mm | 159 | 30.4 |
| 4833-3 | 30-45mm | 0.1mm | ±0.1mm | 166 | 45.4 |
| 4833-4 | 45-60mm | 0.1mm | ±0.1mm | 170 | 60.5 |


TAPER GAGE SET



4837-1

When measure diameter of hole

When measuring diameter of holes, correction on reading is needed due to the thickness of taper gage. For example, when reading A is 14.96mm, diameter ØD is 15mm.




| | include 4pcs | | |
|----|------------------|-------------|---------------------|
| | (1-8mm, 8-15mm, | 15-22mm, | 22-29mm) |
| | Measure opening, | slot width, | hole diameter, etc. |
| 86 | D' | - 4-61 | Ale - le le |

Diameter correction table on the back

Made of stainless steel

- Indicate Asses





| Code | Range | Graduation | Accuracy |
|--------|--------|------------|----------|
| 4837-1 | 1-29mm | 0.05mm | ±0.05mm |

WELDING GAGE



4830





- Made of stainless steel
- Stain chrome plated reading surface

| Code | Measurement | Range | Graduation | Accuracy |
|------|-------------------------|--------------------|------------|----------|
| 4830 | crown height | 0-8mm | 0.1mm | ±0.1mm |
| | fillet weld throat size | 0-20mm | 0.1mm | ±0.3mm |
| | angle | 60°, 70°, 80°, 90° | _ | ±1° |