PORTABLE LEEB HARDNESS TESTER CODE ISH-PHB

SPECIFICATION

Min. reading	1HLD, 1HV, 1HB, 0.1HRC, 0.1HRB, 1HS, 1MPa			
Accuracy	±6HLD (when HLD=800)			
Display		converted hardness, material, tion, test times, average value, date		
Output	bluetooth			
Applicable workpiece	minimum weight	5kg		
		2kg (on solid support)		
		0.1kg (coupled on plate)		
	minimum thickness: 5mm			
	minimum radius of curved surface: 30mm			
	maximum roughness (Ra): 1.6µm			
Power supply	3×AAA batteries			
Dimension	150×84×28mm			
Weight	200g			



- Based on Leeb (HLD), converted to Vickers (HV), Brinell (HB), Rockwell (HRC and HRB), Shore (HS) and tensile strength (MPa)

 • Memory of 99 measurement values for browsing
- Set measurement times (1~9) to have average value
- Connected with printer via bluetooth
- Automatic power off
- According to ASTM A 956







(optional)

STANDARD DELIVERY

Main unit	1pc
Impact device D	1pc
Hardness test block D	1pc
Small support ring	1pc
Cleaning brush	1pc

OPTIONAL ACCESSORY

OF HONAL ACCESSOR				
Wireless printer	ISH-DS-PRINTER			
Couplant	ISH-COUPLANT			
Support rings	see details			
Hardness test block D	ISH-BHLD			

APPLICABLE MATERIAL AND HARDNESS RANGE FOR IMPACT DEVICE D

Material	HLD	HV	НВ	HRC	HRB	HS	Tensile strength (MPa)
Steel & cast steel	300-900	81-955	81-654	20-68	38-100	32-100	375-2639
Tool steel	300-840	80-898		20-67			
Stainless steel	300-800	85-802	85-655		46-101		
Cast iron	360-650		93-334				
Cast aluminum alloy	170-570		19-164		23-84		
Brass	200-550		40-173		13-95		
Bronze	300-700		60-290				
Copper	200-690		45-315				

- Impact device D
- Based on Leeb (HLD), converted to Vickers (HV), Brinell (HB), Rockwell (HRC and HRB), Shore (HS) and tensile strength (MPa)
- Automatic direction correction
- Connected with printer via bluetooth
- Connected with computer via USB port
- Up to 500 test results can be saved
- According to ASTM A 956



CODE ISH-SPHD DATA OUTPUT



PORTABLE LEEB HARDNESS TESTER

CRECIFICATION

Min. reading	1HLD, 1HV, 1HB, 0.1HRC, 0.1HRB, 1HS			
Accuracy	±6HLD (when HLD=800)			
Output	USB and bluetooth			
Applicable workpiece	minimum weight	5kg (direct measurement)		
		2kg (on solid support)		
		0.1kg (coupled on plate)		
	minimum thickness: 5mm			
	minimum radius of curved surface: 30mm			
	maximum roughness (Ra): 1.6µm			
Power supply	built-in rechargeable battery			
Dimension	147×35×22mm			
Weight	65a			

printer (included)

hardness test block D (included)



small support ring (included)

APPLICABLE MATERIAL AND HARDNESS RANGE FOR IMPACT DEVICE D

Material	HLD	HV	НВ	HRC	HRB	HS
Steel & cast steel	300-900	81-955	81-654	20-68	38-100	32-100
Tool steel	300-840	80-898		20-67		
Stainless steel	300-800	85-802	85-655		46-101	
Cast iron	360-650		93-334			
Cast aluminum alloy	170-570		19-164		23-84	
Brass	200-550		40-173		13-95	
Bronze	300-700		60-290			
Copper	200-690		45-315			

STANDARD DELIVERY

Main unit	1pc	
Printer	1pc	
Hardness test block D	1pc	
Small support ring	1pc	
Cleaning brush	1pc	
AC/DC adapter	1pc	
USB cable and software disc	1pc	

OPTIONAL ACCESSORY

Couplant	ISH-COUPLANT
Support rings	see details
Hardness test block D	ISH-BHLD