HIGH MAGNIFICATION MICROSCOPE CODE ISM-M1000**

- For high magnification observation
 Kohler illumination system provides uniform illumination field
- Objectives 20X, 40X, 100X are spring type

STANDARD DELIVERY

Main unit	1pc
Oil for 100X objective	1bottle
Anti-dust cover	1pc
Filter (blue/green/yellow)	1pc of each



SPECIFICATION

Eyepiece (wide field)	10X (view field: Ø18mm)				
Objective (plan achromatic)	10X	20X	40X	100X (oil type)	
Numerical aperture	0.25	0.40	0.60	1.25	
Working distance	8.8mm	8.6mm	3.3mm	0.33mm	
	double layer				
Stage	size: 180×150mm				
	travel: 15×15mm				
Pupil distance	53~75mm				
Diopter adjustment	±5 diopter (one eyepiece)				
Illumination	6V/20W halogen lamp				
Power supply	220V, 5	0/60Hz **	e		
Dimension (L×W×H)	385×30	0×440mm			
Weight	11kg				

Add "-U" on code No. when power supply is 110V, 50/60Hz

OPTIONAL ACCESSORY

	PL50X	ISM-MTM-OB50X
Objective	PL60X	ISM-MTM-OB60X
Objective	PL80X	ISM-MTM-OB80X
	PL100X (dry type)	ISM-MTM-OB100X
10X dividing	eyepiece (0.1mm/div.)	ISM-MTM-EPD10X
WF16X eyer	piece	ISM-MTM-EP16X
WF20X eyer	piece	ISM-MTM-EP20X
Camera ada	pter (1X)	ISM-M1000-ADAPTER
Digital came	era	ISM-D500

DIGITAL CAMERA CODE ISM-D500



- Inserted into eyepiece tube or camera connecter of microscopes
- Supplied with software







SPECIFICATION

Sensor	1/2.5" CMOS
Pixel	5M
Resolution	2592×1944 or 1296×972
*************	3fps (2592×1944)
Frame rate	12fps (1296×972)
Exposure	manual or auto, exposure time is adjustable
SNR	41dB
Power supply	USB
Weight	400g


STANDARD DELIVERY

Main unit	1pc
Adapter 0.45X	1pc
Calibration rule (graduation 0.1mm)	1pc
Connector Ø23.2/Ø30mm	1pc
USB cable	1pc
Software disc	1pc



OPTIONAL ACCESSORY

Connector Ø23.2/Ø30.5mm ISM-DCA-CON



graduation 0.1mm)


SOFTWARE FOR DIGITAL CAMERA (INCLUDED)

Measuring Tools:

measure distance between two points

measure rectangle

calibration



measure circle

- Can take pictures and videos
- Exposure/gain/gamma/saturation/colour adjustment
 Image process feature: zoom in/out, image flip and so on

