

SHORT HANDLE DIGITAL TORQUE WRENCHES

- Clockwise and counter-clockwise operation
- Unit: N.m, in.lb, ft.lb, kg.cm
- Peak and track working mode
- Target torque value can be set, with audible and visible alarm:
 - Green LED light on and buzzer sounds when torque value is 90%~100% of target torque
 - Both green and red LED light on and buzzer sounds when target torque value is reached
- Power off in 5 minutes automatically
- Non-slip grip handle
- With damp record
- With overload record (once the torque reaches 110% of the maximum range)



IST-WS60

SPECIFICATION

Code	IST-WS30	IST-WS30A	IST-WS60	IST-WS85
Range	6~30N.m	6~30N.m	12~60N.m	17~85N.m
Accuracy	clockwise	±3%		
	counter-clockwise	±4%		
Resolution	0.01N.m	0.01N.m	0.01N.m	0.1N.m
Square driver (L)	1/4"	3/8"	3/8"	3/8"
Power supply	2×AAA batteries			
Length	215mm	215mm	225mm	271mm
Weight	750g	830g	917g	1000g



VIDEO

OPTIONAL ACCESSORY

Calibration cable IST-SD-CABLE

WIRELESS DATA TRANSFER DIGITAL TORQUE WRENCHES

- Wireless data transfer to computer
- Unit: N.m, in.lb, ft.lb, kg.cm
- Clockwise and counter-clockwise operation
- Peak and track working mode
- Can set tolerance with judgement in peak working mode
- 9 target torque values can be set, with audible and visible alarm:
 - Green LED light on and buzzer sounds when torque value is 80%~99.5% of target torque
 - Both green and red LED light on and buzzer sounds when torque value is over 99.5% of target torque
- Power off in 2 minutes automatically
- Non-slip grip handle
- With damp record
- With overload record (once the torque reaches 110% of the maximum range)



DIGITAL TORQUE WRENCH
IST-3W135A



VIDEO



RECEIVER
IST-3WREC

DIGITAL TORQUE WRENCH SPECIFICATION

Code		IST-3W30A	IST-3W135A	IST-3W200A	IST-3W340A
Range		6~30N.m	27~135N.m	40~200N.m	68~340N.m
Accuracy	clockwise	±2%			
	counter-clockwise	±3%			
Tolerance setting range		-25% ~ +25% (target torque value)			
Resolution		0.01N.m	0.1N.m	0.1N.m	0.1N.m
Square driver (L)		1/4"	3/8"	1/2"	1/2"
Working frequency		ISM433MHz (432.0~433.8MHz, adjustable)			
Power supply		2xAA batteries, for 110 hours working			
Length		390mm	415mm	530mm	650mm
Weight		760g	940g	1340g	1540g

RECEIVER SPECIFICATION

Code	IST-3WREC
Working frequency	ISM433MHz (432.0~433.8MHz adjustable)
Power supply	DC 24V, 0.5A
Dimension	200×108×31mm
Weight	500g

OPTIONAL ACCESSORY

Calibration cable IST-SD-CABLE

