

PIPE VIDEOSCOPE CODE ISV-VP280

SPECIFICATION

Lens	diameter	28mm
	dust/waterproof	IP68
	pixel	0.3M
	resolution	640×480
	frame	30fps
Cable	length	22m
	dust/waterproof	IP68
	type	semi-rigid
Main unit	function	take picture and video
	file format	picture: JPG, video: ASF
	image process	mirror, rotate, zoom (1.5X, 2X)
	memory	4G SD card
	output	TV, USB
	power supply	4×AA batteries
Weight		5kg



ATTENTION: RESISTANCE TO ACID AND ALKALI LIQUID (CONSULT IS NEEDED)

IP68
WATERPROOF



lens with adjustable LED illumination



3.5" LCD

take picture
take video

power
on/off

cable
length: 22m

stand


indicator of
working cable
length



Ø100mm brush (included)
fixed on the lens to clean
the internal wall of pipes




Ø50mm centering ring
(optional) fixed on the lens
to center lens in the pipe



focus distance



angle of view



can turn at least
two times in the
pipe (>Ø40mm)

OPTIONAL ACCESSORY

Ø50mm centering ring	ISV-VP280-R50
Ø150mm brush	ISV-VP280-B150



vertical horizontal

STANDARD DELIVERY

Main unit	1pc
Cable with lens	1pc
Stand	1pc
4G SD card	1pc
Ø100mm brush	1pc
AA battery	4pcs
AAA battery	2pcs
Video output cable	1pc
USB cable	1pc


RIGID BORESCOPIES

- Focus distance: 2mm, depth of view: 5~100mm
- Dust/waterproof level: IP67
- Can be used in the liquid with temperature -10°C~85°C




ISV-1H4300

IP67
WATERPROOF




focus distance angle of view

view direction 0°



focus distance view direction angle of view

view direction 30° and 70°



focus distance angle of view

view direction 90°

SPECIFICATION

Code	Length (L)	View direction (α)	Diameter (D)	Angle of view (θ)
ISV-1H4170	174mm	0°	4mm	≥60°
ISV-1H4173	174mm	30°		
ISV-1H4177	174mm	70°		
ISV-1H4179	166mm	90°		
ISV-1H4300	302mm	0°		
ISV-1H4303	302mm	30°		
ISV-1H4307	302mm	70°		
ISV-1H4309	297mm	90°		

Code	Length (L)	View direction (α)	Diameter (D)	Angle of view (θ)
ISV-1H6200	209mm	0°	6mm	≥70°
ISV-1H6203	209mm	30°		
ISV-1H6207	209mm	70°		
ISV-1H6209	166mm	90°		
ISV-1H6320	328mm	0°		
ISV-1H6323	328mm	30°		
ISV-1H6327	328mm	70°		
ISV-1H6329	330mm	90°		

OPTIONAL ACCESSORY

LED light handle	ISV-1HLED
Adjustable LED light source	ISV-1LED1
Camera	ISV-1CAM



LED light handle
(optional)



adjustable LED light source
(optional)



camera (optional)