



## Kombi-Aufsteckfräserdorne DIN 6358

Combi shell mill holders DIN 6358

Porte-fraises à double usage DIN 6358

DIN 2080



### Verwendung:


Zur Aufnahme von Walzen-, Walzenstirnfräsern oder Messerköpfen mit Längs- oder Quernut.

### Application:

For mounting milling cutters with transverse or longitudinal groove.

### Application:

Pour le serrage de fraises à rainure transversale ou à rainure longitudinale.



DIN 2080

$\nabla \leq 0,005$

G6,3  
15.000 min<sup>-1</sup>

CAD

Bestell-Nr.  
Order no.  
Référence

SK

$d_{h6}$

A

$l_1$

D

301.10.16

SK 30

16

35

17

32

301.10.22

SK 30

22

35

19

40

301.10.27

SK 30

27

35

21

48

301.10.32

SK 30

32

50

24

58

401.10.16

SK 40

16

52

17

32

401.10.22

SK 40

22

52

19

40

401.10.27

SK 40

27

52

21

48

401.10.32

SK 40

32

52

24

58

401.10.40

SK 40

40

52

27

70

501.10.16

SK 50

16

55

17

32

501.10.22

SK 50

22

55

19

40

501.10.27

SK 50

27

55

21

48

501.10.32

SK 50

32

55

24

58

501.10.40

SK 50

40

55

27

70

**Lieferumfang:** Mit Fräseranzugsschraube, Mitnehmerring und Passfeder  
**Delivery:** With tightening bolt, driving ring and feather key  
**Livraison:** Avec vis de blocage, bague d'entraînement et clavette

