


CARBIDE, 2 FLUTE SHORT LENGTH BALL NOSE
VOLLHARTMETALL, 2 SCHNEIDEN KURZ STIRNRADIUS


Unit : mm

EDP No.	Radius of Ball Nose	Mill Diameter	Shank Diameter	Length of Cut	Overall Length
FLAT	R (±0.02)	h10	h6		
E5437020	R1.0	2.0	6	3	50
E5437030	R1.5	3.0	6	4	50
E5437040	R2.0	4.0	6	5	54
E5437050	R2.5	5.0	6	6	54
E5437060	R3.0	6.0	6	7	54
E5437080	R4.0	8.0	8	9	58
E5437100	R5.0	10.0	10	11	66
E5437120	R6.0	12.0	12	12	73
E5437140	R7.0	14.0	14	14	75
E5437180	R9.0	18.0	18	18	84
E5437200	R10.0	20.0	20	20	92

▶ TiN, TiCN-COATING & TiAlN-COATING are available on your request.

Tolerances according to DIN 7160 & 7161
Toleranzen nach DIN 7160 & 7161

Tolerance range in μm / Toleranzwerte in μm					
Nominal-Diameter in mm / Nennmaßbereich in mm					
	from 1 to 3 von 1 bis 3	over 3 to 6 über 3 bis 6	over 6 to 10 über 6 bis 10	over 10 to 18 über 10 bis 18	over 18 to 30 über 18 bis 30
h10	0 - 40	0 - 48	0 - 58	0 - 70	0 - 84
h6	0 - 6	0 - 8	0 - 9	0 - 11	0 - 13


◎ : Excellent ○ : Good

Carbon Steels	Alloy Steels	Prehardened Steels	Hardened Steels		High Hardened Steels	Copper	Graphite	Cast Iron	Aluminum	Stainless Steels	Titanium	Inconel	Acrylic	CFRP
~HB225	HB225~325	HRc30~40	HRc40~45	HRc45~55	HRc55~70									
◎	◎	◎	○					○	○					

CARBIDE, 2 FLUTE BALL NOSE
VOLLHARTMETALL, 2 SCHNEIDEN STIRNRADIUS

E5624, E5650, E5437, E5438, E5454, E5455 SERIES

MATERIAL	CARBON STEELS ALLOY STEELS TOOL STEELS				CARBON STEELS ALLOY STEELS TOOL STEELS				CAST IRON				ALUMINUM ALLOYS			
	HARDNESS	~ HRc30				HRc30 ~ HRc40										
STRENGTH	~ 1000N/mm ²				1000 ~ 1300N/mm ²											
DIAMETER	RPM	FEED	Vc	fz	RPM	FEED	Vc	fz	RPM	FEED	Vc	fz	RPM	FEED	Vc	fz
R1.0 × 2.0	5200	90	35	0.009	4400	45	30	0.005	7300	150	45	0.010	21500	280	135	0.007
R1.5 × 3.0	3500	100	35	0.014	2900	45	25	0.008	4900	160	45	0.016	14300	280	135	0.010
R2.0 × 4.0	2600	100	35	0.019	2100	45	25	0.011	3600	200	45	0.028	10900	280	135	0.013
R2.5 × 5.0	2100	105	35	0.025	1700	45	25	0.013	2900	230	45	0.040	8800	330	140	0.019
R3.0 × 6.0	1700	100	30	0.029	1430	45	25	0.016	2400	250	45	0.052	7260	330	135	0.023
R4.0 × 8.0	1270	95	30	0.037	1100	45	30	0.020	1800	320	45	0.089	5500	380	140	0.035
R5.0 × 10.0	1000	95	30	0.048	870	45	25	0.026	1430	320	45	0.112	4300	380	135	0.044
R6.0 × 12.0	870	85	35	0.049	730	45	30	0.031	1200	320	45	0.133	3600	440	135	0.061
R7.0 × 14.0	750	85	35	0.057	620	45	25	0.036	1000	325	45	0.163	3000	440	130	0.073
R8.0 × 16.0	650	85	35	0.065	540	45	25	0.042	920	325	45	0.177	2700	380	135	0.070
R9.0 × 18.0	580	85	35	0.073	480	45	25	0.047	810	325	45	0.201	2400	380	135	0.079
R10.0 × 20.0	500	85	30	0.085	430	45	25	0.052	730	290	45	0.199	2100	380	130	0.090




※ The FEED, in long & extra long types, should be reduced by around 50%

RPM = rev./min. Vc = m/min.
FEED = mm/min. fz = mm/t

CARBIDE, 2 FLUTE BALL NOSE TiAlN-COATED
VOLLHARTMETALL, 2 SCHNEIDEN STIRNRADIUS TiAlN-BESCHICHTET

E5624, E5650, E5437, E5438, E5454, E5455 SERIES

MATERIAL	CARBON STEELS ALLOY STEELS TOOL STEELS				CARBON STEELS ALLOY STEELS TOOL STEELS				CAST IRON				ALUMINUM ALLOYS			
	HARDNESS	~ HRc30				HRc30 ~ HRc40										
STRENGTH	~ 1000N/mm ²				1000 ~ 1300N/mm ²											
DIAMETER	RPM	FEED	Vc	fz	RPM	FEED	Vc	fz	RPM	FEED	Vc	fz	RPM	FEED	Vc	fz
R1.0 × 2.0	7280	125	45	0.009	6160	65	40	0.005	10220	210	65	0.010	30100	390	190	0.006
R1.5 × 3.0	4900	140	45	0.014	4060	65	40	0.008	6860	225	65	0.016	20020	390	190	0.010
R2.0 × 4.0	3640	140	45	0.019	2940	65	35	0.011	5040	280	65	0.028	15260	390	190	0.013
R2.5 × 5.0	2940	145	45	0.025	2380	65	35	0.014	4060	320	65	0.039	12320	460	195	0.019
R3.0 × 6.0	2380	140	45	0.029	2000	65	40	0.016	3360	350	65	0.052	10165	460	190	0.023
R4.0 × 8.0	1780	135	45	0.038	1540	65	40	0.021	2520	450	65	0.089	7700	530	195	0.034
R5.0 × 10.0	1400	135	45	0.048	1220	65	40	0.027	2000	450	65	0.113	6020	530	190	0.044
R6.0 × 12.0	1220	120	45	0.049	1020	65	40	0.032	1680	450	65	0.134	5040	615	190	0.061
R7.0 × 14.0	1050	120	45	0.057	870	65	40	0.037	1400	455	60	0.163	4200	615	185	0.073
R8.0 × 16.0	910	120	45	0.066	755	65	40	0.043	1290	455	65	0.176	3780	530	190	0.070
R9.0 × 18.0	810	120	45	0.074	670	65	40	0.049	1135	455	65	0.200	3360	530	190	0.079
R10.0 × 20.0	700	120	45	0.086	600	65	40	0.054	1020	405	65	0.199	2940	530	185	0.090



※ The FEED, in long & extra long types, should be reduced by around 50%

RPM = rev./min. Vc = m/min.
FEED = mm/min. fz = mm/t