



STRAIGHT SHANK DRILLS

DL505 SERIES

HSS-E, STRAIGHT SHANK TWIST DRILLS for DEEP HOLES HSS-E, SPIRALBOHRER für TIEFLOCH mit ZYLINDERSCHAFT

JOBBER

KURZ

► **Surface treatment** : Steam Tempered(Black Oxide Finish)
► **Application** : Drilling deep holes in non alloy steels, alloy steels, grey cast iron, malleable cast iron, special aluminum or magnesium alloys.

► **Oberflächenbehandlung** : Steam Homo(Schwarzoxidation)
► **Verwendung** : Zum Bohren von legiertem und unlegiertem stahl, Grauguß, Temperguß, Sphäroguß, Druckguß, Alu-Legierungen kurzspanend, Bronze, Messing zäh, Neusilber.



DIN 338 **HSS-E** **38°** **h8** **130°** **P.217**

► **DH100**
worm pattern drills

Unit : mm

EDP No.	Drill Diameter	Flute Length	Overall Length	EDP No.	Drill Diameter	Flute Length	Overall Length
	D1	L1	L2		D1	L1	L2
DL505020	2.0	24	49	DL505047	4.7	47	80
DL505021	2.1	24	49	DL505048	4.8	52	86
DL505022	2.2	27	53	DL505049	4.9	52	86
DL505023	2.3	27	53	DL505050	5.0	52	86
DL505024	2.4	30	57	DL505051	5.1	52	86
DL505025	2.5	30	57	DL505052	5.2	52	86
DL505026	2.6	30	57	DL505053	5.3	52	86
DL505027	2.7	33	61	DL505054	5.4	57	93
DL505028	2.8	33	61	DL505055	5.5	57	93
DL505029	2.9	33	61	DL505056	5.6	57	93
DL505030	3.0	33	61	DL505057	5.7	57	93
DL505031	3.1	36	65	DL505058	5.8	57	93
DL505032	3.2	36	65	DL505059	5.9	57	93
DL505033	3.3	36	65	DL505060	6.0	57	93
DL505034	3.4	39	70	DL505061	6.1	63	101
DL505035	3.5	39	70	DL505062	6.2	63	101
DL505036	3.6	39	70	DL505063	6.3	63	101
DL505037	3.7	39	70	DL505064	6.4	63	101
DL505038	3.8	43	75	DL505065	6.5	63	101
DL505039	3.9	43	75	DL505066	6.6	63	101
DL505040	4.0	43	75	DL505067	6.7	63	101
DL505041	4.1	43	75	DL505068	6.8	69	109
DL505042	4.2	43	75	DL505069	6.9	69	109
DL505043	4.3	47	80	DL505070	7.0	69	109
DL505044	4.4	47	80	DL505071	7.1	69	109
DL505045	4.5	47	80	DL505072	7.2	69	109
DL505046	4.6	47	80	DL505073	7.3	69	109

► TiN(DN505), TiCN(DX505) and TiAlN(DT505) are available on your request.

◎ : Excellent ○ : Good

Carbon Steels	Alloy Steels	Prehardened Steels	Hardened Steels		Cast Iron	Aluminum	Stainless Steels	Titanium	Mild Steels	Copper	Bronze	CFRP
~HB225	HB225~325	HRc30~45	HRc45~55	HRc55~								
◎	◎				○	○			○			



STRAIGHT SHANK DRILLS

DL505 SERIES

HSS-E, STRAIGHT SHANK TWIST DRILLS for DEEP HOLES HSS-E, SPIRALBOHRER für TIEFLOCH mit ZYLINDERSCHAFT

JOBBER
KURZ

▶ **Surface treatment** : Steam Tempered(Black Oxide Finish)
 ▶ **Application** : Drilling deep holes in non alloy steels, alloy steels, grey cast iron, malleable cast iron, special aluminum or magnesium alloys.

▶ **Oberflächenbehandlung** : Steam Homo(Schwarzoxidation)
 ▶ **Verwendung** : Zum Bohren von legiertem und unlegiertem stahl, Grauguß, Temperguß, Sphäroguß, Druckguß, Alu-Legierungen kurzspanend, Bronze, Messing zäh, Neusilber.



DIN 338 HSS-E 38° h8 130° P.217

▶ DH100 worm pattern drills

Unit : mm

EDP No.	Drill Diameter D1	Flute Length L1	Overall Length L2	EDP No.	Drill Diameter D1	Flute Length L1	Overall Length L2
DL505074	7.4	69	109	DL505094	9.4	81	125
DL505075	7.5	69	109	DL505095	9.5	81	125
DL505076	7.6	75	117	DL505096	9.6	87	133
DL505077	7.7	75	117	DL505097	9.7	87	133
DL505078	7.8	75	117	DL505098	9.8	87	133
DL505079	7.9	75	117	DL505099	9.9	87	133
DL505080	8.0	75	117	DL505100	10.0	87	133
DL505081	8.1	75	117	DL505101	10.1	87	133
DL505082	8.2	75	117	DL505102	10.2	87	133
DL505083	8.3	75	117	DL505105	10.5	87	133
DL505084	8.4	75	117	DL505108	10.8	94	142
DL505085	8.5	75	117	DL505110	11.0	94	142
DL505086	8.6	81	125	DL505112	11.2	94	142
DL505087	8.7	81	125	DL505115	11.5	94	142
DL505088	8.8	81	125	DL505118	11.8	94	142
DL505089	8.9	81	125	DL505120	12.0	101	151
DL505090	9.0	81	125	DL505122	12.2	101	151
DL505091	9.1	81	125	DL505125	12.5	101	151
DL505092	9.2	81	125	DL505128	12.8	101	151
DL505093	9.3	81	125	DL505130	13.0	101	151

▶ TiN(DN505), TiCN(DX505) and TiAlN(DT505) are available on your request.

◎ : Excellent ○ : Good

Carbon Steels	Alloy Steels	Prehardened Steels	Hardened Steels		Cast Iron	Aluminum	Stainless Steels	Titanium	Mild Steels	Copper	Bronze	CFRP
~HB225	HB225~325	HRc30~45	HRc45~55	HRc55~								
◎	◎				○	○			○			

CARBIDE

HSS

I-DREAM DRILLS

DREAM DRILLS -GENERAL

DREAM DRILLS -INOX

DREAM DRILLS -ALU

DREAM DRILLS -CFRP

DREAM DRILLS -MQL TYPE

DREAM DRILLS for HARDENED STEELS

GENERAL CARBIDE DRILLS

NC-SPOTTING DRILLS

CENTER DRILLS

MULTI-1 DRILLS

HPD DRILLS

GOLD-P DRILLS

STRAIGHT SHANK DRILLS

TAPER SHANK DRILLS

NC-SPOTTING DRILLS

CENTER DRILLS

SPADE DRILLS

TECHNICAL DATA

HSS-E, DH100 TYPE WORM PATTERN DRILLS, DIN1897, DIN338, DIN340, DIN1869, DIN341
HSS-E, DH100 TYPE WORM PATTERN SPIRALBOHRER, DIN1897, DIN 338, DIN 340, DIN 1869, DIN 341
DL510, DL508, DL509, DL505, DL504, DT600, DT692, DT693, DL608 SERIES

WORK MATERIAL	CARBON STEELS ALLOY STEELS		TOOL STEELS HARDENED STEELS		SOFT GREY CAST IRON		HARD GREY CAST IRON	
	HARDNESS		HARDNESS					
HARDNESS	HRc15 ~ 30		HRc20 ~ 40					
STRENGTH	700 ~ 1000 N/mm ²		800 ~ 1200 N/mm ²					
DRILLING SPEED	13 ~ 18 m/min		8 ~ 13 m/min		20 ~ 25 m/min		7 ~ 12 m/min	
DIAMETER	N	S	N	S	N	S	N	S
2.0	2630	0.03	2100	0.025	4200	0.06	1680	0.05
2.5	2100	0.04	1680	0.03	3300	0.08	1310	0.06
3.0	1680	0.05	1310	0.04	2630	0.10	1050	0.08
4.0	1310	0.06	1050	0.05	2100	0.13	840	0.10
5.0	1050	0.06	840	0.05	1680	0.13	660	0.10
6.0	840	0.08	660	0.06	1310	0.16	530	0.13
8.0	660	0.10	530	0.08	1050	0.20	420	0.17
10.0	530	0.13	420	0.10	840	0.25	330	0.21
13.0	420	0.13	330	0.10	660	0.25	260	0.21
16.0	330	0.15	260	0.13	530	0.30	210	0.25
20.0	260	0.20	210	0.15	420	0.40	170	0.30
25.0	210	0.25	170	0.20	330	0.50	130	0.50
30.0	170	0.25	130	0.20	260	0.50	110	0.50

N = R.P.M

S = Feed per Revolution (mm/rev.)

HSS-E, DH50 TYPE WORM PATTERN DRILLS
HSS-E, DH50 TYPE WORM PATTERN SPIRALBOHRER
DL507 SERIES

WORK MATERIAL	CARBON STEELS ALLOY STEELS		SOFT GREY CAST IRON		ALUMINUM ALLOY	
	HARDNESS		HARDNESS			
HARDNESS	HRc15 ~ 30		HRc20 ~ 40			
STRENGTH	700 ~ 1000 N/mm ²		800 ~ 1200 N/mm ²			
DRILLING SPEED	13 ~ 18 m/min		8 ~ 13 m/min		25 ~ 30 m/min	
DIAMETER	N	S	N	S	N	S
2.0	2630	0.03	4200	0.06	8700	0.04
2.5	2100	0.04	3300	0.08	6950	0.05
3.0	1680	0.05	2630	0.10	5800	0.06
4.0	1310	0.06	2100	0.13	4300	0.08
5.0	1050	0.06	1680	0.13	3500	0.10
6.0	840	0.08	1310	0.16	2900	0.12
8.0	660	0.10	1050	0.20	2200	0.16
10.0	530	0.13	840	0.25	1750	0.20
13.0	420	0.13	660	0.25	1350	0.26

N = R.P.M

S = Feed per Revolution (mm/rev.)