



**STRAIGHT SHANK DRILLS**

**DL509 SERIES**

**HSS-E, STRAIGHT SHANK TWIST DRILLS for DEEP HOLES**  
**HSS-E, SPIRALBOHRER für TIEFLOCH mit ZYLINDERSCHAFT**

**LONG LANG**

► **Application** : Drilling deep holes in non alloy steels, alloy steels, grey cast iron, malleable cast iron, special aluminum or magnesium alloys.

► **Verwendung** : Zum Bohren von legiertem und unlegiertem stahl, Grauguß, Temperguß, Sphäroguß, Druckguß, Alu-Legierungen kurzspanend, Bronze, Messing zäh, Neusilber.



► **DH100 worm pattern drills**

Unit : mm

EDP No.	Drill Diameter	Flute Length	Overall Length	EDP No.	Drill Diameter	Flute Length	Overall Length
	D1	L1	L2		D1	L1	L2
DL509020	2.0	56	85	DL509047	4.7	82	126
DL509021	2.1	56	85	DL509048	4.8	87	132
DL509022	2.2	59	90	DL509049	4.9	87	132
DL509023	2.3	59	90	DL509050	5.0	87	132
DL509024	2.4	62	95	DL509051	5.1	87	132
DL509025	2.5	62	95	DL509052	5.2	87	132
DL509026	2.6	62	95	DL509053	5.3	87	132
DL509027	2.7	66	100	DL509054	5.4	91	139
DL509028	2.8	66	100	DL509055	5.5	91	139
DL509029	2.9	66	100	DL509056	5.6	91	139
DL509030	3.0	66	100	DL509057	5.7	91	139
DL509031	3.1	69	106	DL509058	5.8	91	139
DL509032	3.2	69	106	DL509059	5.9	91	139
DL509033	3.3	69	106	DL509060	6.0	91	139
DL509034	3.4	73	112	DL509061	6.1	97	148
DL509035	3.5	73	112	DL509062	6.2	97	148
DL509036	3.6	73	112	DL509063	6.3	97	148
DL509037	3.7	73	112	DL509064	6.4	97	148
DL509038	3.8	78	119	DL509065	6.5	97	148
DL509039	3.9	78	119	DL509066	6.6	97	148
DL509040	4.0	78	119	DL509067	6.7	97	148
DL509041	4.1	78	119	DL509068	6.8	102	156
DL509042	4.2	78	119	DL509069	6.9	102	156
DL509043	4.3	82	126	DL509070	7.0	102	156
DL509044	4.4	82	126	DL509071	7.1	102	156
DL509045	4.5	82	126	DL509072	7.2	102	156
DL509046	4.6	82	126	DL509073	7.3	102	156

i-DREAM DRILLS

DREAM DRILLS -GENERAL

DREAM DRILLS -INOX

DREAM DRILLS -ALU

DREAM DRILLS -CFRP

DREAM DRILLS -MQL TYPE

DREAM DRILLS for HARDENED STEELS

GENERAL CARBIDE DRILLS

NC-SPOTTING DRILLS

CENTER DRILLS

MULTI-1 DRILLS

HPD DRILLS

GOLD-P DRILLS

STRAIGHT SHANK DRILLS

TAPER SHANK DRILLS

NC-SPOTTING DRILLS

CENTER DRILLS

SPADE DRILLS

TECHNICAL DATA

Carbon Steels	Alloy Steels	Prehardened Steels	Hardened Steels		Cast Iron	Aluminum	Stainless Steels	Titanium	Mild Steels	Copper	Bronze	CFRP
~HB225	HB225~325	HRc30~45	HRc45~55	HRc55~								
◎	◎				○	○			○			



# STRAIGHT SHANK DRILLS

**DL509** SERIES

## HSS-E, STRAIGHT SHANK TWIST DRILLS for DEEP HOLES HSS-E, SPIRALBOHRER für TIEFLOCH mit ZYLINDERSCHAFT

**LONG LANG**

► **Application** : Drilling deep holes in non alloy steels, alloy steels, grey cast iron, malleable cast iron, special aluminum or magnesium alloys.

► **Verwendung** : Zum Bohren von legiertem und unlegiertem stahl, Grauguß, Temperguß, Sphäroguß, Druckguß, Alu-Legierungen kurzspanend, Bronze, Messing zäh, Neusilber.



DIN 340

HSS-E

42°

h8

130°



P.217

► **DH100**  
worm pattern drills

Unit : mm

EDP No.	Drill Diameter	Flute Length L1	Overall Length L2	EDP No.	Drill Diameter	Flute Length L1	Overall Length L2
	D1				D1		
DL509074	7.4	102	156	DL509090	9.0	115	175
DL509075	7.5	102	156	DL509091	9.1	115	175
DL509076	7.6	109	165	DL509092	9.2	115	175
DL509077	7.7	109	165	DL509093	9.3	115	175
DL509078	7.8	109	165	DL509094	9.4	115	175
DL509079	7.9	109	165	DL509095	9.5	115	175
DL509080	8.0	109	165	DL509096	9.6	121	184
DL509081	8.1	109	165	DL509097	9.7	121	184
DL509082	8.2	109	165	DL509098	9.8	121	184
DL509083	8.3	109	165	DL509099	9.9	121	184
DL509084	8.4	109	165	DL509100	10.0	121	184
DL509085	8.5	109	165	DL509102	10.2	121	184
DL509086	8.6	115	175	DL509105	10.5	121	184
DL509087	8.7	115	175	DL509110	11.0	128	195
DL509088	8.8	115	175	DL509115	11.5	128	195
DL509089	8.9	115	175	DL509120	12.0	134	205

◎ : Excellent ○ : Good

Carbon Steels	Alloy Steels	Prehardened Steels	Hardened Steels		Cast Iron	Aluminum	Stainless Steels	Titanium	Mild Steels	Copper	Bronze	CFRP
~HB225	HB225~325	HRc30~45	HRc45~55	HRc55~								
◎	◎				○	○			○			

**HSS-E, DH100 TYPE WORM PATTERN DRILLS, DIN1897, DIN338, DIN340, DIN1869, DIN341**  
**HSS-E, DH100 TYPE WORM PATTERN SPIRALBOHRER, DIN1897, DIN 338, DIN 340, DIN 1869, DIN 341**
**DL510, DL508, DL509, DL505, DL504, DT600, DT692, DT693, DL608** SERIES

WORK MATERIAL	CARBON STEELS ALLOY STEELS		TOOL STEELS HARDENED STEELS		SOFT GREY CAST IRON		HARD GREY CAST IRON	
	HARDNESS		HARDNESS					
HARDNESS	HRc15 ~ 30		HRc20 ~ 40					
STRENGTH	700 ~ 1000 N/mm <sup>2</sup>		800 ~ 1200 N/mm <sup>2</sup>					
DRILLING SPEED	13 ~ 18 m/min		8 ~ 13 m/min		20 ~ 25 m/min		7 ~ 12 m/min	
DIAMETER	N	S	N	S	N	S	N	S
2.0	2630	0.03	2100	0.025	4200	0.06	1680	0.05
2.5	2100	0.04	1680	0.03	3300	0.08	1310	0.06
3.0	1680	0.05	1310	0.04	2630	0.10	1050	0.08
4.0	1310	0.06	1050	0.05	2100	0.13	840	0.10
5.0	1050	0.06	840	0.05	1680	0.13	660	0.10
6.0	840	0.08	660	0.06	1310	0.16	530	0.13
8.0	660	0.10	530	0.08	1050	0.20	420	0.17
10.0	530	0.13	420	0.10	840	0.25	330	0.21
13.0	420	0.13	330	0.10	660	0.25	260	0.21
16.0	330	0.15	260	0.13	530	0.30	210	0.25
20.0	260	0.20	210	0.15	420	0.40	170	0.30
25.0	210	0.25	170	0.20	330	0.50	130	0.50
30.0	170	0.25	130	0.20	260	0.50	110	0.50

N = R.P.M

S = Feed per Revolution (mm/rev.)

**HSS-E, DH50 TYPE WORM PATTERN DRILLS**  
**HSS-E, DH50 TYPE WORM PATTERN SPIRALBOHRER**
**DL507** SERIES

WORK MATERIAL	CARBON STEELS ALLOY STEELS		SOFT GREY CAST IRON		ALUMINUM ALLOY	
	HARDNESS		HARDNESS			
HARDNESS	HRc15 ~ 30					
STRENGTH	700 ~ 1000 N/mm <sup>2</sup>					
DRILLING SPEED	13 ~ 18 m/min		25 ~ 30 m/min		45 ~ 55 m/min	
DIAMETER	N	S	N	S	N	S
2.0	2630	0.03	4200	0.06	8700	0.04
2.5	2100	0.04	3300	0.08	6950	0.05
3.0	1680	0.05	2630	0.10	5800	0.06
4.0	1310	0.06	2100	0.13	4300	0.08
5.0	1050	0.06	1680	0.13	3500	0.10
6.0	840	0.08	1310	0.16	2900	0.12
8.0	660	0.10	1050	0.20	2200	0.16
10.0	530	0.13	840	0.25	1750	0.20
13.0	420	0.13	660	0.25	1350	0.26

N = R.P.M

S = Feed per Revolution (mm/rev.)