

2 FLUTE, SHORT LENGTH, CORNER RADIUS

G9B82 SERIES

PLAIN SHANK

- ▶ Suitable for dry milling applications at high temperatures.
- ▶ Excellent high-performance end mills.
- ▶ 2 flute design for slotting.



MULTI PURPOSE



P.51



Unit : mm



EDP No.	MILL DIAMETER	CORNER RADIUS	SHANK DIAMETER	LENGTH OF CUT	OVERALL LENGTH
G9B82020	2.0	R0.2	4	4	50
G9B82901	2.0	R0.3	4	4	50
G9B82902	2.0	R0.5	4	4	50
G9B82025	2.5	R0.2	4	5	50
G9B82903	2.5	R0.3	4	5	50
G9B82904	2.5	R0.5	4	5	50
G9B82030	3.0	R0.2	4	6	50
G9B82905	3.0	R0.3	4	6	50
G9B82906	3.0	R0.5	4	6	50
G9B82907	3.0	R1.0	4	6	50
G9B82040	4.0	R0.2	4	8	50
G9B82908	4.0	R0.3	4	8	50
G9B82909	4.0	R0.5	4	8	50
G9B82910	4.0	R1.0	4	8	50
G9B82050	5.0	R0.2	6	10	50
G9B82911	5.0	R0.3	6	10	50
G9B82912	5.0	R0.5	6	10	50
G9B82913	5.0	R1.0	6	10	50
G9B82060	6.0	R0.2	6	12	50
G9B82914	6.0	R0.3	6	12	50
G9B82915	6.0	R0.5	6	12	50
G9B82916	6.0	R1.0	6	12	50
G9B82080	8.0	R0.5	8	16	60
G9B82917	8.0	R1.0	8	16	60
G9B82918	8.0	R1.5	8	16	60
G9B82919	8.0	R2.0	8	16	60
G9B82920	8.0	R2.5	8	16	60
G9B82100	10.0	R0.5	10	20	75
G9B82921	10.0	R1.0	10	20	75
G9B82922	10.0	R1.5	10	20	75
G9B82923	10.0	R2.0	10	20	75
G9B82924	10.0	R2.5	10	20	75
G9B82120	12.0	R0.5	12	24	75
G9B82925	12.0	R1.0	12	24	75
G9B82926	12.0	R1.5	12	24	75
G9B82927	12.0	R2.0	12	24	75
G9B82928	12.0	R2.5	12	24	75

MILL DIA. TOLERANCE(mm)	SHANK DIA. TOLERANCE
0 - 0.030	h6

2 FLUTE, FINISH, SLOTTING

▶ G9B82, G9B83 Series

MATERIAL	NON-ALLOYED STEELS, ALLOY STEELS, TOOL STEELS		ALLOY STEELS, HEAT RESISTANT STEELS		STAINLESS STEELS		CAST IRON		ALUMINUM ALLOYS		COPPER. BRASS NON-FERROUS METALS	
HARDNESS	~ HRc 30		HRc 30 ~ HRc 45									
STRENGTH	~ 1000N/mm ²		1000 ~ 1500N/mm ²									
DIAMETER	RPM	FEED	RPM	FEED	RPM	FEED	RPM	FEED	RPM	FEED	RPM	FEED
1	14300	105	8500	65	7150	50	18700	205	44000	330	24700	200
1.5	9350	150	5550	85	5600	80	12100	205	27500	385	20300	300
2	7850	160	5150	100	4300	80	9350	220	22000	460	16500	340
3	6100	180	3800	120	3150	100	6050	220	15400	460	11000	340
4	5150	255	3150	155	2650	130	4600	220	11000	460	8800	340
5	4300	270	2550	160	2150	135	3650	220	9150	460	6800	340
6	3800	300	2300	190	1950	155	2950	255	7600	485	5700	375
8	2850	325	1700	170	1450	155	2200	275	5700	485	4400	375
10	2200	280	1350	135	1150	135	1850	285	4600	485	3400	375
12	1850	240	1150	110	950	110	1450	295	3750	485	2850	375



※ The FEED, in long & extra long types, should be reduced by around 50%

RPM = rev./min. Feed = mm/min.