



# HSS-E, SIDE AND FACE MILLING CUTTERS with STRAIGHT TEETH HSS-E, SCHEIBENFRÄSER mit GERADEVERZAHNT

► The tools are used for general purpose side and straddle milling where deep cut is not required.

► Diese Werkzeuge werden bei allgemeinen Seiten- und Breitfräsen eingesetzt, wo Tiefschnitte nicht vorkommen.




HSS-E
DIN 885-B
H
P.1290

Unit : mm

EDP No.	Cutter Diameter	Width of Face	Internal Diameter	No. of Teeth
	D(js14)	S(k11)	d(H7)	Z
ML09205001	50.0	4	16	18
ML09205002	50.0	5	16	18
ML09205003	50.0	6	16	18
ML09205004	50.0	8	16	16
ML09205005	50.0	10	16	16
ML09206301	63.0	5	22	22
ML09206302	63.0	6	22	22
ML09206303	63.0	8	22	20
ML09206304	63.0	10	22	20
ML09206305	63.0	12	22	20
ML09208001	80.0	6	22	24
ML09208002	80.0	8	22	24
ML09208003	80.0	10	22	24
ML09208004	80.0	12	22	20
ML09208005	80.0	6	27	24
ML09208006	80.0	8	27	24
ML09208007	80.0	10	27	24
ML09208008	80.0	12	27	20
ML09210001	100.0	6	27	26
ML09210002	100.0	8	27	26
ML09210003	100.0	10	27	22
ML09210004	100.0	6	32	26
ML09210005	100.0	8	32	26
ML09210006	100.0	10	32	22
ML09210007	100.0	12	32	22
ML09212501	125.0	8	32	30
ML09212502	125.0	10	32	30
ML09212503	125.0	12	32	24

**Tolerances according to DIN 7160 & 7161  
Toleranzen nach DIN 7160 & 7161**

	Nominal-Diameter in mm / Nennmaßbereich in mm							
	over 3 to 6 über 3 bis 6	over 6 to 10 über 6 bis 10	over 10 to 18 über 10 bis 18	over 18 to 30 über 18 bis 30	over 30 to 50 über 30 bis 50	over 50 to 80 über 50 bis 80	over 80 to 120 über 80 bis 120	over 120 to 180 über 120 bis 180
Tolerance range in mm / Toleranzwerte mm								
js14	± 0.15	± 0.18	± 0.215	± 0.26	± 0.31	± 0.37	± 0.435	± 0.50
Tolerance range in µm / Toleranzwerte in µm								
k11	+ 75 0	+ 90 0	+ 110 0	+ 130 0	+ 160 0	+ 190 0	+ 220 0	+ 250 0
H7	+ 12 0	+ 15 0	+ 18 0	+ 21 0	+ 25 0	+ 30 0	+ 35 0	+ 40 0



Carbon Steels	Alloy Steels	Prehardened Steels	Hardened Steels	High Hardened Steels	Copper	Graphite	Cast Iron	Aluminum	Stainless Steels	Titanium	Inconel	Acrylic	CFRP
~HB225	HB225~325	HRC30~40	HRC40~45 HRc45~55	HRc55~70									
◎	◎	○						○					


HSS-E, SIDE AND FACE MILLING CUTTERS WITH STRAIGHT TEETH  
HSS-E, SCHEIBENFRÄSER mit GERADEVERZAHNT

**ML092** SERIES

MATERIAL	CARBON STEELS ALLOY STEELS				CARBON STEELS ALLOY STEELS TOOL STEELS				CARBON STEELS ALLOY STEELS TOOL STEELS			
HARDNESS					~ HRc20				HRc20 ~ HRc30			
STRENGTH	~ 500N/mm <sup>2</sup>				500 ~ 800N/mm <sup>2</sup>				800 ~ 1000N/mm <sup>2</sup>			
DIAMETER	RPM	FEED	Vc	fz	RPM	FEED	Vc	fz	RPM	FEED	Vc	fz
50.0	160	130	25	0.045	115	82	20	0.040	95	58	15	0.034
63.0	125	160	25	0.058	90	72	20	0.036	75	51	15	0.031
80.0	100	145	25	0.060	70	69	20	0.041	60	48	15	0.033
100.0	80	130	25	0.063	60	60	20	0.038	47	41	15	0.034
125.0	63	100	25	0.066	45	54	20	0.050	38	38	15	0.042

MATERIAL	CARBON STEELS ALLOY STEELS TOOL STEELS				ALUMINUM & ALUMINUM ALLOYS			
HARDNESS	HRc30 ~ HRc40							
STRENGTH	1000 ~ 1300N/mm <sup>2</sup>							
DIAMETER	RPM	FEED	Vc	fz	RPM	FEED	Vc	fz
50.0	76	42	10	0.031	630	200	100	0.018
63.0	60	38	10	0.029	500	250	100	0.023
80.0	47	34	10	0.030	400	250	100	0.026
100.0	38	30	10	0.030	320	200	100	0.024
125.0	30	26	10	0.036	250	200	100	0.033

RPM = rev./min.  
FEED = mm/min.  
Vc = m/min.  
fz = mm/t



MILLING DEPTH P = WIDTH OF FACES

CBN  
END MILLS

i-Xmill  
END MILLS

i-HS mill  
END MILLS

X5070  
END MILLS

4G MILL  
END MILLS

X-SPEED  
ROUGHER  
END MILLS

X-POWER  
END MILLS

JET-POWER  
END MILLS

TN MILL  
END MILLS

V7 Mill  
END MILLS

ALU-POWER  
END MILLS

CRX S  
END MILLS

D-POWER  
GRAPHITE  
END MILLS

D-POWER  
CFRP  
END MILLS

ROUTERS

K-2 CARBIDE  
END MILLS

GENERAL  
CARBIDE  
END MILLS

TANK-POWER  
END MILLS

GENERAL  
HSS  
END MILLS

MILLING  
CUTTERS

TECHNICAL  
DATA