


### M Solid Carbide Thread Mill with Coolant Hole & Chamfer for ISO Metric Internal Thread - DIN 13 VOLLHARTMETALL GEWINDEFÄSER mit KÜHLKANAL & FASE für METRISCHES INNENGEWINDE - DIN 13


► Easy to cut threads even if exotic materials like Nickel, Titanium or their alloys.

► Problemloses Gewindeschneiden sogar in exotischen Werkstoffen, wie Nickel, Titan und ihre Legierungen.



- Material : Solid Carbide
- Shank : DIN6535 HA
- Spiral Angle : 15°
- Thread Length : 2 × D

- Material : Vollhartmetall
- Schaft : DIN 6535 HA
- Drallwinkel : 15°
- Gewindelänge : 2 × D



Unit : mm

EDP No.	Nominal Diameter [ D ]	Pitch P	Cutter Diameter D <sub>1</sub>	Shank Diameter D <sub>2</sub>	Thread Length L <sub>1</sub>	Over All Length L <sub>2</sub>	Angle A	No. of Flute Z
L4271310	M6	1.0	4.8	8	12.4	62	90°	3
L4271360	M8	1.25	6.5	10	16.8	74	90°	3
L4271420	M10	1.5	8.2	12	20.15	80	90°	4
L4271500	M12	1.75	9.9	14	25.25	90	90°	4
L4271540	M14	2.0	11.6	16	28.85	100	90°	4
L4271600	M16	2.0	13.6	18	32.85	102	90°	4

\* Other coatings are available on your request

Carbon Steels	Alloy Steels	Heat Treated Steels	High Hardened Steel	Cast Iron	Stainless Steels	Titanium Alloy	Chrome-Nickel Alloy	Non Ferrous Materials
◎	◎	◎		◎	○	○	○	◎

◎ : Excellent ○ : Good

**RECOMMENDED CUTTING SPEED**  
**EMPFOHLENE SCHNEIDKONDITIONEN**
**RECOMMENDED CUTTING CONDITION for Thread Mills**

unit : mm

Materials	Cutting Speed (m/min)	Feed per Tooth (fz)	
		Cutter Diameter ≤ Ø8.0	Cutter Diameter > Ø8.0
Low Carbon Steels Medium Carbon Steels	80 - 120	0.02 - 0.04	0.04 - 0.10
High Carbon Steels	80 - 120	0.02 - 0.04	0.04 - 0.10
Alloy Steels	80 - 120	0.02 - 0.04	0.04 - 0.10
Heat Treated Steels	60 - 100	0.02 - 0.04	0.04 - 0.10
Stainless Steels	40 - 80	0.01 - 0.02	0.02 - 0.06
Cast Iron	50 - 100	0.02 - 0.04	0.04 - 0.10
Chrome-Nickel Alloys Titanium Alloys	20 - 60	0.01 - 0.02	0.02 - 0.06
Non Ferrous Materials	100 - 300	0.03 - 0.07	0.05 - 0.10

**RECOMMENDED CUTTING CONDITION for Drill and Thread Mills**

unit : mm

Material	Cutting Speed (m/min)	Fz(Thread Milling) - Feed per tooth		Fdr(Drilling) - Feed per revolution	
		Cutter Diameter ≤ Ø8.0	Cutter Diameter > Ø8.0	Cutter Diameter ≤ Ø8.0	Cutter Diameter > Ø8.0
Cast Iron	80-150	0.03-0.08	0.08-0.12	0.10-0.20	0.20-0.25
Aluminium Aluminium-alloy Magnesium	100-300	0.05-0.10	0.10-0.15	0.10-0.20	0.20-0.30
Plastics	80-150	0.05-0.10	0.10-0.15	0.10-0.20	0.20-0.30

**RECOMMENDED CUTTING CONDITION  
for Hard Material Miniature Thread Mills**

unit : mm

Materials	Cutting Speed (m/min)	Feed(mm/tooth)	
		Cutter Diameter ≤ Ø6.0	Cutter Diameter > Ø6.0
Alloy Steel ≥ HB325	80-120	0.02-0.04	0.04-0.06
Stainless Steel ≥ HB330	40-80	0.02-0.04	0.04-0.06
Cast Iron	50-100	0.03-0.05	0.05-0.07
Chrome-Nickel Alloys Titanium Alloys	20-60	0.02-0.03	0.03-0.05
Hardened Material	45~50HRc	25-70	0.03-0.05
	51~55HRc	25-60	0.02-0.04
	56~62HRc	25-50	0.01-0.03