

Turning · Drehen

Threading tools · Gewindedrehwerkzeuge


A

Parting & Grooving · Ab- & Einstechen



Threading · Gewindedrehen

General pitch thread insert (partial profil)
Allgemeiner Einsatz (Teilprofil)


Thin Type





R



		Type · Typ	Dimension (mm) Abmessung					Grade · Sorte
		Right hand Rechtsausführung	Pitch · Steigung (T.P.i)	S	ØI.C	ød	α°	YBG202
External · Außen	60°	RT16.01W-A60B	0.5-1.5(48-16)	3.52	9.525	4.0	60°	●
		RT16.01W-G60B	1.75-3.0(14-8)	3.52	9.525	4.0	60°	
		RT16.01W-AG60B	0.5-3.0(48-8)	3.52	9.525	4.0	60°	●
	55°	RT16.01W-A55B	0.5-1.5(48-16)	3.52	9.525	4.0	55°	●
		RT16.01W-G55B	1.75-3.0(14-8)	3.52	9.525	4.0	55°	●
		RT16.01W-AG55B	0.5-3.0(48-8)	3.52	9.525	4.0	55°	●



R



		Type · Typ	Dimension (mm) Abmessung					Grade · Sorte
		Right hand Rechtsausführung	Pitch · Steigung (T.P.i)	S	ØI.C	ød	α°	YBG202
Internal · Innen	60°	RT16.01N-A60B	0.5-1.5(48-16)	3.52	9.525	4.0	60°	●
		RT16.01N-G60B	1.75-3.0(14-8)	3.52	9.525	4.0	60°	●
		RT16.01N-AG60B	0.5-3.0(48-8)	3.52	9.525	4.0	60°	●
	55°	RT16.01N-A55B	0.5-1.5(48-16)	3.52	9.525	4.0	55°	●
		RT16.01N-G55B	1.75-3.0(14-8)	3.52	9.525	4.0	55°	●
		RT16.01N-AG55B	0.5-3.0(48-8)	3.52	9.525	4.0	55°	●

● ex stock · ab Lager ○ on demand · auf Anfrage