




British standard taper pipe thread insert
Rohrgewinde für Dampf-, Gas- und Wasserleitungen

Thin Type

ISO 7/1:1994, B.S.21:1985
Standard BSPT




R



	Type · Typ	Dimension (mm) · Abmessung				Grade · Sorte
	Right hand Rechtersausführung	Pitch · Steigung (T.P.i)	S	ØI.C	ød	YBG202
External · Außen	RT16.01W-11BSPTB	11	3.52	9.525	4.0	●
	RT16.01W-14BSPTB	14	3.52	9.525	4.0	●
	RT16.01W-19BSPTB	19	3.52	9.525	4.0	●
	RT16.01W-28BSPTB	28	3.52	9.525	4.0	●



R



	Type · Typ	Dimension (mm) · Abmessung				Grade · Sorte
	Right hand Rechtersausführung	Pitch · Steigung (T.P.i)	S	ØI.C	ød	YBG202
Internal · Innen	RT16.01N-11BSPTB	11	3.52	9.525	4.0	●
	RT16.01N-14BSPTB	14	3.52	9.525	4.0	●
	RT16.01N-19BSPTB	19	3.52	9.525	4.0	●
	RT16.01N-28BSPTB	28	3.52	9.525	4.0	●

● ex stock · ab Lager ○ on demand · auf Anfrage