



ISO metric thread insert (full profile)
Allgemeiner Einsatz (Vollprofil)


Thin Type

ISO 965-1980, DIN 13, GB/T 197-2003


tolerances: 6g/6H




R



	Type · Typ	Dimension (mm) Abmessung				Grade · Sorte
	Right hand Rechtsausführung	Pitch-Steigung (T.P.i)	S	ØI.C	ød	YBG202
External · Außen	RT16.01W-0.50GMB	0.50	3.52	9.525	4.0	●
	RT16.01W-0.75GMB	0.75	3.52	9.525	4.0	●
	RT16.01W-1.00GMB	1.00	3.52	9.525	4.0	●
	RT16.01W-1.25GMB	1.25	3.52	9.525	4.0	●
	RT16.01W-1.50GMB	1.50	3.52	9.525	4.0	●
	RT16.01W-1.75GMB	1.75	3.52	9.525	4.0	●
	RT16.01W-2.00GMB	2.00	3.52	9.525	4.0	●
	RT16.01W-2.50GMB	2.50	3.52	9.525	4.0	●
	RT16.01W-3.00GMB	3.00	3.52	9.525	4.0	●



R



	Type · Typ	Dimension (mm) Abmessung				Grade · Sorte
	Right hand Rechtsausführung	Pitch-Steigung (T.P.i)	S	ØI.C	ød	YBG202
Internal · Innen	RT16.01N-0.50GMB	0.50	3.52	9.525	4.0	●
	RT16.01N-0.75GMB	0.75	3.52	9.525	4.0	●
	RT16.01N-1.00GMB	1.00	3.52	9.525	4.0	●
	RT16.01N-1.25GMB	1.25	3.52	9.525	4.0	●
	RT16.01N-1.50GMB	1.50	3.52	9.525	4.0	●
	RT16.01N-1.75GMB	1.75	3.52	9.525	4.0	●
	RT16.01N-2.00GMB	2.00	3.52	9.525	4.0	●
	RT16.01N-2.50GMB	2.50	3.52	9.525	4.0	●
	RT16.01N-3.00GMB	3.00	3.52	9.525	4.0	●

● ex stock · ab Lager ○ on demand · auf Anfrage