



UN full profile · UN Vollprofil


ASME B1.1-1989
tolerances: 2A · 2B



R




L




	Type · Typ		Dimension (mm) Abmessung				Grade · Sorte	
	Right hand Rechtsausführung	Left hand Linksausführung	Pitch · Steigung (T.P.i.)	S	ØI.C	ød	YBG201	
							R	L
External · Außen	RT16.01W-8UN	LT16.01W-8UN	8	3.97	9.525	4.4	○	○
	RT16.01W-10UN	LT16.01W-10UN	10	3.97	9.525	4.4	●	●
	RT16.01W-12UN	LT16.01W-12UN	12	3.97	9.525	4.4	●	●
	RT16.01W-14UN	LT16.01W-14UN	14	3.97	9.525	4.4	●	●
	RT16.01W-16UN	LT16.01W-16UN	16	3.97	9.525	4.4	●	●
	RT16.01W-18UN	LT16.01W-18UN	18	3.97	9.525	4.4	●	●
	RT16.01W-20UN	LT16.01W-20UN	20	3.97	9.525	4.4	●	●



R



L



	Type · Typ		Dimension (mm) Abmessung				Grade · Sorte	
	Right hand Rechtsausführung	Left hand Linksausführung	Pitch · Steigung (T.P.i.)	S	ØI.C	ød	YBG201	
							R	L
Internal · Innen	RT16.01N-8UN	LT16.01N-8UN	8	3.97	9.525	4.4	○	○
	RT16.01N-10UN	LT16.01N-10UN	10	3.97	9.525	4.4	●	●
	RT16.01N-12UN	LT16.01N-12UN	12	3.97	9.525	4.4	●	●
	RT16.01N-14UN	LT16.01N-14UN	14	3.97	9.525	4.4	●	●
	RT16.01N-16UN	LT16.01N-16UN	16	3.97	9.525	4.4	●	●
	RT16.01N-18UN	LT16.01N-18UN	18	3.97	9.525	4.4	●	●
	RT16.01N-20UN	LT16.01N-20UN	20	3.97	9.525	4.4	●	●
	RT16.01N-24UN	LT16.01N-24UN	24	3.97	9.525	4.4	●	●

● ex stock · ab Lager ○ on demand · auf Anfrage