



Turning · Drehen

Threading tools · Gewindedrehwerkzeuge


UN full profile
UN Vollprofil

Thin Type


ASME B1.1-1989
tolerances: 2A/2B




R



	Type · Typ	Dimension (mm) Abmessung				Grade · Sorte
	Right hand Rechtausführung	Pitch · Steigung (T.P.i)	S	ØI.C	ød	YBG202
External · Außen	RT16.01W-8UNB	8	3.52	9.525	4.0	●
	RT16.01W-10UNB	10	3.52	9.525	4.0	●
	RT16.01W-12UNB	12	3.52	9.525	4.0	●
	RT16.01W-14UNB	14	3.52	9.525	4.0	●
	RT16.01W-16UNB	16	3.52	9.525	4.0	●
	RT16.01W-18UNB	18	3.52	9.525	4.0	●
	RT16.01W-20UNB	20	3.52	9.525	4.0	●



R



	Type · Typ	Dimension (mm) · Abmessung				Grade · Sorte
	Right hand Rechtausführung	Pitch · Steigung (T.P.i)	S	ØI.C	ød	YBG202
Internal · Innen	RT16.01N-8UNB	8	3.52	9.525	4.0	●
	RT16.01N-10UNB	10	3.52	9.525	4.0	●
	RT16.01N-12UNB	12	3.52	9.525	4.0	●
	RT16.01N-14UNB	14	3.52	9.525	4.0	●
	RT16.01N-16UNB	16	3.52	9.525	4.0	●
	RT16.01N-18UNB	18	3.52	9.525	4.0	●
	RT16.01N-20UNB	20	3.52	9.525	4.0	●
	RT16.01N-24UNB	24	3.52	9.525	4.0	●

● ex stock · ab Lager ○ on demand · auf Anfrage