


Turning · Drehen


Threading tools · Gewindedrehwerkzeuge

Whitworth thread insert
Whitworth Rohrgewinde


ISO 228-1:1982,
DIN 259, B.S.84:1956
tolerances: Medium class A



R




L




	Type · Typ		Dimension (mm) Abmessung				Grade · Sorte	
	Right hand Rechtsausführung	Left hand Linksausführung	Pitch · Steigung (T.P.i.)	S	ØI.C.	ød	YBG201	
							R	L
External · Außen	RT16.01W-8W	LT16.01W-8W	8	3.97	9.525	4.4	●	●
	RT16.01W-9W	LT16.01W-9W	9	3.97	9.525	4.4	●	●
	RT16.01W-10W	LT16.01W-10W	10	3.97	9.525	4.4	●	●
	RT16.01W-11W	LT16.01W-11W	11	3.97	9.525	4.4	●	●
	RT16.01W-12W	LT16.01W-12W	12	3.97	9.525	4.4	●	●
	RT16.01W-14W	LT16.01W-14W	14	3.97	9.525	4.4	●	●
	RT16.01W-16W	LT16.01W-16W	16	3.97	9.525	4.4	●	●



R



L



	Type · Typ		Dimension (mm) Abmessung				Grade · Sorte	
	Right hand Rechtsausführung	Left hand Linksausführung	Pitch · Steigung (T.P.i.)	S	ØI.C.	ød	YBG201	
							R	L
Internal · Innen	RT16.01N-8W	LT16.01N-8W	8	3.97	9.525	4.4	●	●
	RT16.01N-9W	LT16.01N-9W	9	3.97	9.525	4.4	●	●
	RT16.01N-10W	LT16.01N-10W	10	3.97	9.525	4.4	●	●
	RT16.01N-11W	LT16.01N-11W	11	3.97	9.525	4.4	●	●
	RT16.01N-12W	LT16.01N-12W	12	3.97	9.525	4.4	●	●
	RT16.01N-14W	LT16.01N-14W	14	3.97	9.525	4.4	●	●
	RT16.01N-16W	LT16.01N-16W	16	3.97	9.525	4.4	●	●

● ex stock · ab Lager ○ on demand · auf Anfrage