




Whitworth thread insert
Whitworth Rohrgewinde

Thin Type


ISO 228/1:1982, DIN 259, B.S.84:1956
tolerances: Medium class A




R



	Type · Typ	Dimension (mm) · Abmessung				Grade · Sorte
	Right hand Rechtausführung	Pitch · Steigung (T.P.i)	S	ØI.C	ød	YBG202
External · Außen	RT16.01W-8WB	8	3.52	9.525	4.0	●
	RT16.01W-9WB	9	3.52	9.525	4.0	●
	RT16.01W-10WB	10	3.52	9.525	4.0	●
	RT16.01W-11WB	11	3.52	9.525	4.0	●
	RT16.01W-12WB	12	3.52	9.525	4.0	●
	RT16.01W-14WB	14	3.52	9.525	4.0	●
	RT16.01W-16WB	16	3.52	9.525	4.0	●



R



	Type · Typ	Dimension (mm) · Abmessung				Grade · Sorte
	Right hand Rechtausführung	Pitch · Steigung (T.P.i)	S	ØI.C	ød	YBG202
Internal · Innen	RT16.01N-8WB	8	3.52	9.525	4.0	●
	RT16.01N-9WB	9	3.52	9.525	4.0	●
	RT16.01N-10WB	10	3.52	9.525	4.0	●
	RT16.01N-11WB	11	3.52	9.525	4.0	●
	RT16.01N-12WB	12	3.52	9.525	4.0	●
	RT16.01N-14WB	14	3.52	9.525	4.0	●
	RT16.01N-16WB	16	3.52	9.525	4.0	●

● ex stock · ab Lager ○ on demand · auf Anfrage